



### Main

Commercial Status	Commercialised
Range of product	TeSys F
Product or component type	Contacteur coil
Device short name	LX1FX
Control circuit type	AC 40...400 Hz
Control circuit voltage	220...240 V AC 40...400 Hz
Average resistance	920 Ohm holding at 20 °C 19.5 Ohm inrush at 20 °C
Inductance of closed circuit	0.82 H
Product compatibility	LC1F780
Operating time	40...80 ms closing 130...230 ms opening
Mechanical durability	5 Mcycles
Operating rate	600 cyc/h at <= 55 °C

### Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.2...0.4 Uc at 55 °C drop-out 40...400 Hz 0.85...1.1 Uc at 55 °C operational 40...400 Hz
Inrush power in VA	2100 VA at 20 °C (cos φ 0.9) 40...400 Hz
Hold-in power consumption in VA	50 VA at 20 °C (cos φ 0.3) 40...400 Hz
Heat dissipation	44 W at 40...400 Hz

### Environment

Ambient air temperature for operation	> -5...55 °C
Product weight	3 kg
Quantity per set	Set of 2

### Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.