



Main

Commercial Status	Commercialised
Range of product	GV7
Product or component type	Auxiliary contact block
Product compatibility	GV7RE GV7RS
Pole contact composition	1 C/O

Complementary

Auxiliary contacts operation	Standard
[Ui] rated insulation voltage	690 V - for control circuit - conforming to IEC 60947-1
[Ue] rated operational voltage	690 V AC for control circuit 48 V DC for control circuit 48 V AC for control circuit 440 V AC for control circuit 380...415 V AC for control circuit 250 V DC for control circuit 24 V DC for control circuit 24 V AC for control circuit 230...240 V AC for control circuit 110 V DC for control circuit 110 V AC for control circuit
Mechanical durability	50000 cycles
Minimum switching current	5 mA for control circuit
Minimum switching voltage	17 V for control circuit
Connections - terminals	Control circuit: connector 1 cable 1.5 mm ² - cable stiffness: solid Control circuit: connector 1 cable 1.5 mm ² - cable stiffness: flexible - without cable end Control circuit: connector 1 cable 1.5 mm ² - cable stiffness: flexible - with cable end
Product weight	0.015 kg

Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.