





## Main

|   |  |
|---|--|
| Range of product                            | TeSys K  |
| Product or component type                   | Contactor  |
| Device short name                           | LP1K   |
| Contactor application                       | Resistive load   |
| Utilisation category                        | AC-1   |
| Poles description                           | 4P   |
| Power pole contact composition              | 2 NO + 2 NC  |
| [Ue] rated operational voltage              | 690 V AC 50/60 Hz for power circuit  |
| [Ie] rated operational current              | 16 A (<= 70 °C) at 690 V AC AC-1 for power circuit<br>20 A (<= 50 °C) at <= 440 V AC AC-1 for power circuit  |
| Control circuit type                        | DC standard  |
| Control circuit voltage                     | 24 V DC  |
| [Uimp] rated impulse withstand voltage      | 8 kV   |
| Overvoltage category                        | III  |
| [Ith] conventional free air thermal current | 20 A at <= 50 °C for power circuit   |
| Irms rated making capacity                  | 110 A AC for power circuit conforming to IEC 60947<br>110 A AC for power circuit conforming to NF C 63-110   |
| Rated breaking capacity                     | 70 A at 660...690 V conforming to IEC 60947<br>110 A at 380...400 V conforming to IEC 60947<br>110 A at 220...230 V conforming to IEC 60947<br>80 A at 500 V conforming to IEC 60947<br>110 A at 440 V conforming to IEC 60947<br>110 A at 415 V conforming to IEC 60947   |
| [Icw] rated short-time withstand current    | 20 A <= 50 °C >= 15 s power circuit<br>40 A <= 50 °C 3 min power circuit<br>45 A <= 50 °C 1 min power circuit<br>60 A <= 50 °C 30 s power circuit<br>80 A <= 50 °C 10 s power circuit<br>85 A <= 50 °C 5 s power circuit<br>90 A <= 50 °C 1 s power circuit  |
| Associated fuse rating                      | 25 A aM for power circuit<br>25 A gG at <= 440 V for power circuit   |
| Average impedance                           | 3 mOhm at 50 Hz - Ith 20 A for power circuit   |
| [Ui] rated insulation voltage               | 600 V for power circuit conforming to CSA C22.2 No 14<br>690 V for power circuit conforming to IEC 60947-4-1<br>600 V for power circuit conforming to UL 508   |
| Electrical durability                       | 0.18 Mcycles 20 A AC-1 at Ue <= 440 V  |
| Mounting support                            | Plate<br>Rail  |
| Standards                                   | BS 5424<br>IEC 60947<br>NF C 63-110<br>VDE 0660  |
| Product certifications                      | CSA<br>UL  |
| Connections - terminals                     | Screw clamp terminals 2 cable(s) 0.34...1.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Screw clamp terminals 2 cable(s) 0.75...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Screw clamp terminals 2 cable(s) 1.5...4 mm <sup>2</sup> - cable stiffness: solid<br>Screw clamp terminals 1 cable(s) 0.34...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Screw clamp terminals 1 cable(s) 0.75...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Screw clamp terminals 1 cable(s) 1.5...4 mm <sup>2</sup> - cable stiffness: solid |

|                          |  |
|--------------------------|--|
| Tightening torque        | 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2  |
| Operating time           | 15 ms coil de-energisation and NC closing<br>25...35 ms coil energisation and NC opening<br>10 ms coil de-energisation and NO opening<br>30...40 ms coil energisation and NO closing |
| Safety reliability level | B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1<br>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1                 |
| Mechanical durability    | 10 Mcycles   |
| Operating rate           | 3600 cyc/h   |

## Complementary

|                                |   |
|--------------------------------|---|
| Control circuit voltage limits | 0.1...0.75 U <sub>c</sub> at ≤ 50 °C drop-out<br>0.8...1.15 U <sub>c</sub> at ≤ 50 °C operational |
| Inrush power in W              | 3 W at 20 °C  |
| Hold-in power consumption in W | 3 W at 20 °C  |
| Heat dissipation               | 3 W   |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP2x conforming to VDE 0106   |
| Protective treatment                  | TC conforming to DIN 50016<br>TC conforming to IEC 60068  |
| Ambient air temperature for operation | -25...50 °C   |
| Ambient air temperature for storage   | -50...80 °C   |
| Operating altitude                    | 2000 m without derating in temperature  |
| Flame retardance                      | Requirement 2 conforming to NF F 16-102<br>Requirement 2 conforming to NF F 16-101<br>V1 conforming to UL 94  |
| Mechanical robustness                 | Shocks contactor closed, on Y axis 10 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor closed, on X axis 15 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor opened, on Y axis 6 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor opened, on X axis 10 Gn for 11 ms IEC 60068-2-27<br>Vibrations contactor opened 2 Gn, 5...300 Hz IEC 60068-2-6<br>Vibrations contactor closed 4 Gn, 5...300 Hz IEC 60068-2-6<br>Shocks contactor opened, on Z axis 10 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor closed, on Z axis 15 Gn for 11 ms IEC 60068-2-27 |
| Height                                | 58 mm   |
| Width                                 | 45 mm   |
| Depth                                 | 57 mm   |
| Product weight                        | 0.225 kg  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS                             | Compliant - since 0633 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                     |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|