Product data sheet Characteristics

LUFV2

TeSys U - LUF function block indication of motor load 4...20 mA

Main

Commercial Status	Commercialised
Range of product	TeSys U
Device short name	LUF
Product or component type	Function module
Product compatibility	LUCB LUCC LUCD LUCM

Complementary

Mounting mode	Plug-in
Mounting location	Front side
Main function available	Indication of motor load
[Us] rated supply voltage	24 V DC
Analogue output current	4.2 mA
Type of output signal	Value of I average/Ir ratio within the range of 0 to 2 for LUCB and LUCD Value of I average/Ir ratio within the range of 0 to 3 for LUCC
Load impedance ohmic	100 Ohm typical <= 500 Ohm
Measurement accuracy	+/- 6 % with advanced control unit +/- 10 % with multifunction control unit - resolution: 1 % of Ir
Connection pitch	3.81 mm
Connections - terminals	Screw clamp terminals 2 cable 0.5 mm² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.250.34 mm² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.140.75 mm² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.140.5 mm² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.251 mm² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.250.5 mm² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.141 mm² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.141 mm² - cable stiffness: flexible - without cable end
Associated cable type	AWG 26AWG 16
Tightening torque	0.20.25 N.m - with screwdriver 2.5 mm flat
Product weight	0.05 kg

Contractual warranty

Period	18 months