



Main

Commercial Status	Commercialised
Device short name	LUL
Range of product	TeSys U
Product or component type	Communication module
Product compatibility	LUCA LUCB LUCC LUCD LUCL LUCM

Complementary

Main function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	RS485 multidrop
Bus type	Modbus
Cable connector type	RJ45 front panel
Communication port protocol	Modbus RTU
Addressing	0...31
Transmission rate	19200 bit/s
Return time	30 ms
Number of inputs	2
Input logic	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 1 10 ms +/- 30 % change to state 0
Input type	Resistive
Number of outputs	2 dedicated to starter-controller coil operation 1
Output supply	24 V DC network
Output current	<= 500 mA
Protection type	GG fuse 1 A
Switching current capacity	0.5 mA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	3.81 mm
Connections - terminals	Screw clamp terminals 2 cable 0.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.25...0.34 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.14...0.75 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.14...0.5 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.25...1 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.25...0.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: flexible - without cable end
Associated cable type	AWG 26...AWG 16

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Tightening torque	0.2...0.25 N.m - with screwdriver 2.5 mm
Product weight	0.08 kg

Environment

Ambient air temperature for operation	-25...55 °C
---------------------------------------	-------------
