

LU6MB0FU

reverser block LU6 - 32 A - 110...240 V DC/AC
50...60 Hz - separated mounting



Main

Commercial Status	Commercialised
Range of product	TeSys U
Device short name	LU6MB
Product or component type	Reverser block

Complementary

Mounting mode	Rail
[Ue] rated operational voltage	690 V 500 V 440 V 230 V
Network frequency	40...60 Hz
Duration of inrush phase	25 ms for AC network 50/60 Hz 15 ms for DC network
Operating time	75 ms without change of direction 150 ms with change of direction
[Uc] control circuit voltage	110...240 V AC 110...220 V DC
Current consumption	1000 mA at 110...240 V AC I maximum while closing 1000 mA at 110...220 V DC I maximum while closing
[Ui] rated insulation voltage	600 V conforming to CSA C22.2 No 14 690 V conforming to IEC 60947-1 600 V conforming to UL 508
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-6-2
Connections - terminals	Power circuit: screw clamp terminals 2 cable 1.5...6 mm ² - external diameter: 4 mm - cable stiffness: flexible - without cable end Power circuit: screw clamp terminals 2 cable 1...6 mm ² - external diameter: 4 mm - cable stiffness: rigid - without cable end Power circuit: screw clamp terminals 2 cable 1...6 mm ² - external diameter: 4 mm - cable stiffness: flexible - with cable end Power circuit: screw clamp terminals 1 cable 2.5...10 mm ² - external diameter: 4 mm - cable stiffness: flexible - without cable end Power circuit: screw clamp terminals 1 cable 1...6 mm ² - external diameter: 4 mm - cable stiffness: flexible - with cable end Power circuit: screw clamp terminals 1 cable 1...10 mm ² - external diameter: 4 mm - cable stiffness: rigid - without cable end Control circuit: screw clamp terminals 2 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: rigid - without cable end Control circuit: screw clamp terminals 2 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 2 cable 0.34...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 1 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: rigid - without cable end Control circuit: screw clamp terminals 1 cable 0.75...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable 0.34...1.5 mm ² - external diameter: 3 mm - cable stiffness: flexible - with cable end

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Tightening torque	Power circuit: 1.9...2.5 N.m - with screwdriver 6 mm Philips No 2 Power circuit: 1.9...2.5 N.m - with screwdriver 6 mm flat Control circuit: 0.8...1.2 N.m - with screwdriver 5 mm Philips No 2 Control circuit: 0.8...1.2 N.m - with screwdriver 5 mm flat
Product weight	0.425 kg

Environment

Standards	CSA C22.2 No 14 type E UL 508 type E with phase barrier IEC 60947-6-3 EN 60947-6-3
Product certifications	ABS ASEFA ATEX BV CCC CSA DNV GL GOST LROS (Lloyds register of shipping) UL
IP degree of protection	IP40 front panel outside connection zone conforming to IEC 60947-1 IP20 other faces conforming to IEC 60947-1 IP20 front panel and wired terminals conforming to IEC 60947-1
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-25...70 °C with LUCA, LUCB, LUCC, LUCD -25...60 °C with LUCM
Fire resistance	960 °C parts supporting live components conforming to IEC 60695-2-12 650 °C conforming to IEC 60695-2-12
Operating altitude	2000 m
Shock resistance	15 gn power poles closed conforming to IEC 60068-2-27 10 gn power poles open conforming to IEC 60068-2-27
Vibration resistance	4 gn 5...300 Hz power poles closed conforming to IEC 60068-2-27 2 gn 5...300 Hz power poles open conforming to IEC 60068-2-27
Resistance to electrostatic discharge	8 kV level 4, on contact conforming to IEC 61000-4-2 8 kV level 3, in open air conforming to IEC 61000-4-2
Resistance to radiated fields	10 V/m level 3 conforming to IEC 61000-4-3
Resistance to fast transients	4 kV class 4 all circuits except for serial link conforming to IEC 61000-4-4 2 kV class 3 serial link conforming to IEC 61000-4-4
Non-dissipating shock wave	2 kV common mode conforming to IEC 60947-6-2 1 kV serial mode conforming to IEC 60947-6-2
Immunity to radioelectric fields	10 V conforming to IEC 61000-4-6