



Main

Commercial Status	Commercialised
Range of product	TeSys U
Device short name	LUF
Product or component type	Communication gateway
Product compatibility	ATS48 ATV31 TeSys U starter-controllers

Complementary

Bus type	DeviceNet Modbus
Type of connector	RJ45 to a PC RJ45 Modbus 1 removable 5-way screw connector field bus
Maximum number of connections	<= 8 Modbus slaves
[Us] rated supply voltage	24 V DC +/- 10 %
Current consumption	280 mA maximum 100 mA typical
Local signalling	LED front panel
Services	Monitoring - bus type: DeviceNet - functions available: 256 configurable words Configuration and adjustment - bus type: Fipio - functions available: by gateway mini messaging facility Command - bus type: DeviceNet - functions available: 256 configurable words
Product weight	0.245 kg

Environment

Electromagnetic compatibility	Electromagnetic immunity conforming to IEC 61000-6-2 Electromagnetic emission conforming to IEC 50081-2
Pollution degree	2 conforming to IEC 60664
Ambient air temperature for installation	5...50 °C
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.