



Main

Commercial Status	Commercialised
Range of product	TeSys VARIO
Device short name	Enclosed switch disconnector
Product or component type	Enclosed switch disconnector
Performance level	High performance
Switch function	With ON/OFF function
Poles description	3P
Network type	AC
[I _{th}] conventional enclosed thermal current	25 A
Suitability for isolation	Yes

Complementary

Handle colour	Black
Handle front plate colour	Black
Rotary handle padlocking	With
Network frequency	50/60 Hz
Control type	Rotary handle
Sealing	Yes
[U _e] rated operational voltage	690 V AC
[U _{imp}] rated impulse withstand voltage	8 kV
[I _e] rated operational current	21.8 A at 400 V AC-23A
Rated operational power in W	11 kW at 400 V AC-23
Intermittent duty class	30
Making capacity	320 A at 400 V (AC-23A) 320 A at 400 V (AC-22A) 320 A at 400 V (AC-21A)
[I _{cm}] rated short-circuit making capacity	1 kA at 400 V at I _{peak}
[I _{cw}] rated short-time withstand current	384 A at 400 V during 1 s
Rated conditional short-circuit current	10 kA at 400 V - associated fuse 35 A gG 10 kA at 400 V - associated fuse 35 A aM
Breaking capacity	250 A at 400 V AC-23A 250 A at 400 V AC-22A 250 A at 400 V AC-21A
Mechanical durability	100000 cycles
Electrical durability	30000 cycles on DC-1...5 100000 cycles on AC-21
Connections - terminals	Control circuit: connector cable 6 mm ² - cable stiffness: flexible - with cable end Control circuit: connector cable 10 mm ² - cable stiffness: solid -
Tightening torque	Control circuit: 2.1 N.m - on connector
Provision for padlocking	Padlockable with upto 3 padlocks (Ø 4 mm to Ø 8 mm shank)
Handle front plate dimension	60 x 60 mm
Height	146 mm
Width	90 mm
Depth	131 mm
Product weight	0.5 kg

Environment

Standards	IEC 60204 IEC 60947-4-1
Product certifications	CSA GL UL
Protective treatment	TC
IP degree of protection	IP65 conforming to IEC 60529
Shock resistance	30 gn conforming to IEC 60068-2-27
Vibration resistance	1 gn conforming to IEC 60068-2-6
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60595-2-1

RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(Y Y W W)	0738

Contractual warranty

Period	18 months
--------	-----------