



Main

Commercial Status	Commercialised
Range of product	TeSys VARIO
Device short name	Main pole module
Product or component type	Add-on modules
Poles description	1P
Network type	AC DC
[I _{th}] conventional free air thermal current	12 A
Suitability for isolation	Yes

Complementary

Network frequency	50/60 Hz
Mounting location	Left
[U _e] rated operational voltage	690 V AC 50/60 Hz
[U _{imp}] rated impulse withstand voltage	8 kV
[I _{the}] conventional enclosed thermal current	10 A

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

1.5 A at 220 V L/R = 1 ms DC-1 1
1.5 A at 110 V L/R = 1 ms DC-5 1
1.5 A at 110 V L/R = 1 ms DC-4 1
1.5 A at 110 V L/R = 1 ms DC-3 1
1.5 A at 110 V L/R = 1 ms DC-2 1
1.5 A at 110 V L/R = 1 ms DC-1 1
1.4 A at 220 V L/R = 1 ms DC-5 2
1.4 A at 220 V L/R = 1 ms DC-4 2
1.4 A at 220 V L/R = 1 ms DC-3 2
1.4 A at 220 V L/R = 1 ms DC-2 2
1.2 A at 250 V L/R = 1 ms DC-5 3
1.2 A at 250 V L/R = 1 ms DC-4 3
1.2 A at 250 V L/R = 1 ms DC-3 3
1.2 A at 250 V L/R = 1 ms DC-2 3
0.6 A at 250 V L/R = 1 ms DC-1 1
0.4 A at 250 V L/R = 1 ms DC-5 2
0.4 A at 250 V L/R = 1 ms DC-4 2
0.4 A at 250 V L/R = 1 ms DC-3 2
0.4 A at 250 V L/R = 1 ms DC-2 2
0.4 A at 220 V L/R = 1 ms DC-5 1
0.4 A at 220 V L/R = 1 ms DC-4 1
0.4 A at 220 V L/R = 1 ms DC-3 1
0.4 A at 220 V L/R = 1 ms DC-2 1
0.3 A at 250 V L/R = 1 ms DC-5 1
0.3 A at 250 V L/R = 1 ms DC-4 1
0.3 A at 250 V L/R = 1 ms DC-3 1
0.3 A at 250 V L/R = 1 ms DC-2 1
8.9 A at 500 V AC-23A
8.6 A at 690 V AC-23A
8.1 A at 415 V AC-23A
8.1 A at 400 V AC-23A
10.6 A at 240 V AC-23A
10.6 A at 230 V AC-23A
8 A at 250 V L/R = 1 ms DC-1 3
8 A at 110 V L/R = 1 ms DC-1 2
7 A at 220 V L/R = 1 ms DC-1 2
3 A at 250 V L/R = 1 ms DC-1 2
3 A at 110 V L/R = 1 ms DC-5 2
3 A at 110 V L/R = 1 ms DC-4 2
3 A at 110 V L/R = 1 ms DC-3 2
3 A at 110 V L/R = 1 ms DC-2 2
12 A at 60 V L/R = 1 ms DC-5 3
12 A at 60 V L/R = 1 ms DC-5 2
12 A at 60 V L/R = 1 ms DC-4 3
12 A at 60 V L/R = 1 ms DC-4 2
12 A at 60 V L/R = 1 ms DC-3 3
12 A at 60 V L/R = 1 ms DC-3 2
12 A at 60 V L/R = 1 ms DC-2 3
12 A at 60 V L/R = 1 ms DC-2 2
12 A at 60 V L/R = 1 ms DC-1 3
12 A at 60 V L/R = 1 ms DC-1 2
12 A at 60 V L/R = 1 ms DC-1 1
12 A at 48 V L/R = 1 ms DC-5 3
12 A at 48 V L/R = 1 ms DC-5 2
12 A at 48 V L/R = 1 ms DC-5 1
12 A at 48 V L/R = 1 ms DC-4 3
12 A at 48 V L/R = 1 ms DC-4 2
12 A at 48 V L/R = 1 ms DC-4 1
12 A at 48 V L/R = 1 ms DC-3 3
12 A at 48 V L/R = 1 ms DC-3 2
12 A at 48 V L/R = 1 ms DC-3 1
12 A at 48 V L/R = 1 ms DC-2 3
12 A at 48 V L/R = 1 ms DC-2 2
12 A at 48 V L/R = 1 ms DC-2 1
12 A at 48 V L/R = 1 ms DC-1 3
12 A at 48 V L/R = 1 ms DC-1 2
12 A at 48 V L/R = 1 ms DC-1 1
12 A at 24 V L/R = 1 ms DC-5 3
12 A at 24 V L/R = 1 ms DC-5 2
12 A at 24 V L/R = 1 ms DC-5 1
12 A at 24 V L/R = 1 ms DC-4 3
12 A at 24 V L/R = 1 ms DC-4 2
12 A at 24 V L/R = 1 ms DC-4 1
12 A at 24 V L/R = 1 ms DC-3 3
12 A at 24 V L/R = 1 ms DC-3 2
12 A at 24 V L/R = 1 ms DC-3 1
12 A at 24 V L/R = 1 ms DC-2 3
12 A at 24 V L/R = 1 ms DC-2 2
12 A at 24 V L/R = 1 ms DC-2 1
12 A at 24 V L/R = 1 ms DC-1 3
12 A at 24 V L/R = 1 ms DC-1 2
12 A at 24 V L/R = 1 ms DC-1 1
12 A at 230...690 V AC-22A
12 A at 230...690 V AC-21A
12 A at 110 V L/R = 1 ms DC-5 3

Rated operational power in W	7.5 kW at 690 V AC-23A 5.5 kW at 690 V AC-3 5.5 kW at 500 V AC-23A 1.5 kW at 230...240 V AC-3 4 kW at 500 V AC-3 4 kW at 415 V AC-23A 4 kW at 400 V AC-23A 3 kW at 400...415 V AC-3 3 kW at 240 V AC-23A 3 kW at 230 V AC-23A
Intermittent duty class	30
Making capacity	120 A at 400 V (AC-23A) 120 A at 400 V (AC-22A) 120 A at 400 V (AC-21A)
[Icm] rated short-circuit making capacity	1 kA at 400 V
[Icw] rated short-time withstand current	300 A at 400 V during 1 s
Rated conditional short-circuit current	10 kA at 400 V - associated fuse 12 A gG 10 kA at 400 V - associated fuse 12 A aM
Breaking capacity	120 A at 400 V AC-23A 120 A at 400 V AC-22A 120 A at 400 V AC-21A
Mechanical durability	100000 cycles
Electrical durability	30000 cycles on DC-5 30000 cycles on DC-4 30000 cycles on DC-3 30000 cycles on DC-2 30000 cycles on DC-1 100000 cycles on AC-21
Connections - terminals	Screw terminals cable 6 mm ² - cable stiffness: flexible - with cable end Screw terminals cable 10 mm ² - cable stiffness: solid -
Tightening torque	2.1 N.m - on screw terminals
Height	74 mm
Width	16 mm
Depth	35 mm
Product weight	0.05 kg

Environment

Standards	IEC 60947-3
Product certifications	CCC CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 with protection shrouds conforming to IEC 60529
Shock resistance	30 gn conforming to IEC 60068-2-27
Vibration resistance	1 gn conforming to IEC 60068-2-6
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

Contractual warranty

Period	18 months
--------	-----------