



Main

Commercial Status	Commercialised
Range of product	TeSys VARIO
Device short name	Main pole module
Product or component type	Add-on modules
Poles description	1P
Network type	AC DC
[I _{th}] conventional free air thermal current	32 A
Suitability for isolation	Yes

Complementary

Network frequency	50/60 Hz
Mounting location	Left
[U _e] rated operational voltage	690 V AC 50/60 Hz
[U _{imp}] rated impulse withstand voltage	8 kV
[I _{the}] conventional enclosed thermal current	25 A

[I_e] rated operational current

0.8 A at 250 V L/R = 1 ms DC-5 1
0.8 A at 250 V L/R = 1 ms DC-4 1
0.8 A at 250 V L/R = 1 ms DC-3 1
0.8 A at 250 V L/R = 1 ms DC-2 1
0.8 A at 220 V L/R = 1 ms DC-5 1
0.8 A at 220 V L/R = 1 ms DC-4 1
0.8 A at 220 V L/R = 1 ms DC-3 1
0.8 A at 220 V L/R = 1 ms DC-2 1
21.8 A at 400 V AC-23A
19.7 A at 230 V AC-23A
18.9 A at 240 V AC-23A
17.5 A at 690 V AC-23A
16.7 A at 500 V AC-23A
8 A at 250 V L/R = 1 ms DC-1 2
6 A at 110 V L/R = 1 ms DC-5 2
6 A at 110 V L/R = 1 ms DC-4 2
6 A at 110 V L/R = 1 ms DC-3 2
6 A at 110 V L/R = 1 ms DC-2 2
4 A at 220 V L/R = 1 ms DC-5 3
4 A at 220 V L/R = 1 ms DC-4 3
4 A at 220 V L/R = 1 ms DC-3 3
4 A at 220 V L/R = 1 ms DC-2 3
32 A at 60 V L/R = 1 ms DC-5 3
32 A at 60 V L/R = 1 ms DC-5 2
32 A at 60 V L/R = 1 ms DC-4 3
32 A at 60 V L/R = 1 ms DC-4 2
32 A at 60 V L/R = 1 ms DC-3 3
32 A at 60 V L/R = 1 ms DC-3 2
32 A at 60 V L/R = 1 ms DC-2 3
32 A at 60 V L/R = 1 ms DC-2 2
32 A at 60 V L/R = 1 ms DC-1 3
32 A at 60 V L/R = 1 ms DC-1 2
32 A at 60 V L/R = 1 ms DC-1 1
32 A at 48 V L/R = 1 ms DC-5 3
32 A at 48 V L/R = 1 ms DC-5 2
32 A at 48 V L/R = 1 ms DC-5 1
32 A at 48 V L/R = 1 ms DC-4 3
32 A at 48 V L/R = 1 ms DC-4 2
32 A at 48 V L/R = 1 ms DC-4 1
32 A at 48 V L/R = 1 ms DC-3 3
32 A at 48 V L/R = 1 ms DC-3 2
32 A at 48 V L/R = 1 ms DC-3 1
32 A at 48 V L/R = 1 ms DC-2 3
32 A at 48 V L/R = 1 ms DC-2 2
32 A at 48 V L/R = 1 ms DC-2 1
32 A at 48 V L/R = 1 ms DC-1 3
32 A at 48 V L/R = 1 ms DC-1 2
32 A at 48 V L/R = 1 ms DC-1 1
32 A at 24 V L/R = 1 ms DC-5 3
32 A at 24 V L/R = 1 ms DC-5 2
32 A at 24 V L/R = 1 ms DC-5 1
32 A at 24 V L/R = 1 ms DC-4 3
32 A at 24 V L/R = 1 ms DC-4 2
32 A at 24 V L/R = 1 ms DC-4 1
32 A at 24 V L/R = 1 ms DC-3 3
32 A at 24 V L/R = 1 ms DC-3 2
32 A at 24 V L/R = 1 ms DC-3 1
32 A at 24 V L/R = 1 ms DC-2 3
32 A at 24 V L/R = 1 ms DC-2 2
32 A at 24 V L/R = 1 ms DC-2 1
32 A at 24 V L/R = 1 ms DC-1 3
32 A at 24 V L/R = 1 ms DC-1 2
32 A at 24 V L/R = 1 ms DC-1 1
32 A at 230...690 V AC-22A
32 A at 230...690 V AC-21A
32 A at 110 V L/R = 1 ms DC-5 3
32 A at 110 V L/R = 1 ms DC-4 3
32 A at 110 V L/R = 1 ms DC-3 3
32 A at 110 V L/R = 1 ms DC-2 3
32 A at 110 V L/R = 1 ms DC-1 3
3 A at 220 V L/R = 1 ms DC-1 1
3 A at 110 V L/R = 1 ms DC-5 1
3 A at 110 V L/R = 1 ms DC-4 1
3 A at 110 V L/R = 1 ms DC-3 1
3 A at 110 V L/R = 1 ms DC-2 1
21 A at 415 V AC-23A
20 A at 60 V L/R = 1 ms DC-5 1
20 A at 60 V L/R = 1 ms DC-4 1
20 A at 60 V L/R = 1 ms DC-3 1
20 A at 60 V L/R = 1 ms DC-2 1
20 A at 220 V L/R = 1 ms DC-1 3
2 A at 250 V L/R = 1 ms DC-5 3
2 A at 250 V L/R = 1 ms DC-4 3
2 A at 250 V L/R = 1 ms DC-3 3
2 A at 250 V L/R = 1 ms DC-2 3

Rated operational power in W	7.5 kW at 500 V AC-3 7.5 kW at 400...415 V AC-3 5.5 kW at 240 V AC-23A 5.5 kW at 230 V AC-23A 4 kW at 230...240 V AC-3 15 kW at 690 V AC-23A 11 kW at 690 V AC-3 11 kW at 500 V AC-23A 11 kW at 415 V AC-23A 11 kW at 400 V AC-23A
Intermittent duty class	30
Making capacity	320 A at 400 V (AC-23A) 320 A at 400 V (AC-22A) 320 A at 400 V (AC-21A)
[Icm] rated short-circuit making capacity	1 kA at 400 V
[Icw] rated short-time withstand current	384 A at 400 V during 1 s
Rated conditional short-circuit current	10 kA at 400 V - associated fuse 35 A gG 10 kA at 400 V - associated fuse 35 A aM
Breaking capacity	250 A at 400 V AC-23A 250 A at 400 V AC-22A 250 A at 400 V AC-21A
Mechanical durability	100000 cycles
Electrical durability	30000 cycles on DC-5 30000 cycles on DC-4 30000 cycles on DC-3 30000 cycles on DC-2 30000 cycles on DC-1 100000 cycles on AC-21
Connections - terminals	Screw terminals cable 6 mm ² - cable stiffness: flexible - with cable end Screw terminals cable 10 mm ² - cable stiffness: solid -
Tightening torque	2.1 N.m - on screw terminals
Height	74 mm
Width	16 mm
Depth	35 mm
Product weight	0.05 kg

Environment

Standards	IEC 60947-3
Product certifications	CCC CSA GL UL
Protective treatment	TC
IP degree of protection	IP20 with protection shrouds conforming to IEC 60529
Shock resistance	30 gn conforming to IEC 60068-2-27
Vibration resistance	1 gn conforming to IEC 60068-2-6
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

Contractual warranty

Period	18 months
--------	-----------