



Distribution units




Name	Color	Part No.
Distribution units 5 pole	gray	on request
	black	96.050.0153.1

Dimensions (W x L x H)	104 x 162 x 57.2 mm
Input	1
Outputs	3
Routing 3 outputs 230/400V, 20A	RST 20i5 coding color black
Prewired with	2.5 mm ²
Fastening options	yes

Circuit diagram







Name	Color	Part No.
RST multi-distribution unit 1 Input, 5 Outputs	black	on request 96.050.2153.1

Detailed information about the distribution units available in section "Distribution units".

Dimensions	104 x 162 x 96 mm
Fitted as required with	M25 device connectors 2 – 5-pole
Input	1
Outputs max.	7
Prewired with	2.5 mm ²
Fuses	6.3 or 10A can be integrated



Accessories

**Female connector
4 to 5 pole**

Color	Part No.	Part No.
gray black	not captive against loss	captive against loss
	Pole 4 – 5 pole	Pole 4 – 5 pole
	Safe locking device unused male connectors	Safe locking device unused male connectors
	05.565.9953.0	99.531.0000.7
	05.565.9953.1	99.532.0000.7

**Male connector
4 to 5 pole**

Color	Part No.	Part No.
gray black	not captive against loss	captive against loss
	Pole 4 – 5 pole	Pole 4 – 5 pole
	Safe locking device unused female connectors	Safe locking device unused female connectors
	Z5.565.9853.0	99.529.0000.7
	Z5.565.9853.1	99.530.0000.7