



M 20 device connector, modular, angled

Female connector

Correct positioning guaranteed due to flattened thread. Fastening with screws from inside.

See the Technical Data for insulation strip lengths as well as the ferrules to be used.



Application	Coding	Color
Power 250 V	L, N, PE	gray black
Power 250/400 V	1, 2, PE	green
Extra-low voltage	1, 2, PE	brown
Switch.func. 250 V	1, 2, 3, PE	light blue

Part No.	with spring clamp conn.
	Wire mm ²
	rigid 0.5 – 2.5
	fine-stranded 0.5 – 1.5
	stranded 0.75 – 1.5
	Term. poles 2
	Thread M20 x 1.5
	Gland inside
96.033.2053.0	
96.033.2053.1	
96.033.2055.7	
96.033.2051.4	
96.033.2053.9	

Fine-stranded and stranded wires **only with** ferrules (see accessories)

Part No.	with screw connection
	Wire mm ²
	rigid
	fine-stranded 0.75 – 6.0
	stranded
	Term. poles 1
	Thread M20 x 1.5
	Gland inside
96.033.6053.0	
96.033.6053.1	
96.033.6055.7	
96.033.6051.4	
96.033.6053.9	

Fine-stranded and stranded wires **without** ferrules

Part No.	with crimp connection
	Wire mm ²
	fine-stranded 0.75 – 4.0 ²⁾
	Term. poles 1
	Thread M20 x 1.5
	Gland inside
96.133.2053.0	
96.133.2053.1	



Contacts separately under Accessories

Male connector

Correct positioning guaranteed due to flattened thread. Fastening with screws from inside.

With locking device.

See the Technical Data for insulation strip lengths.



Application	Coding	Color
Power 250 V	N, L, PE	gray black
Power 250/400 V	2, 1, PE	green
Extra-low voltage	2, 1, PE	brown
Switch.func. 250 V	2, 1, 3, PE	light blue

Part No.	with spring clamp conn.
	Wire mm ²
	rigid 0.5 – 2.5
	fine-stranded 0.5 – 1.5
	stranded 0.75 – 1.5
	Term. poles 2
	Thread M20 x 1.5
	Gland inside
96.034.2053.0	
96.034.2053.1	
96.034.2055.7	
96.034.2051.4	
96.034.2053.9	

Fine-stranded and stranded wires **only with** ferrules (see accessories)

Part No.	with screw connection
	Wire mm ²
	rigid
	fine-stranded 0.75 – 6.0
	stranded
	Term. poles 1
	Thread M20 x 1.5
	Gland inside
96.034.6053.0	
96.034.6053.1	
96.034.6055.7	
96.034.6051.4	
96.034.6053.9	

Fine-stranded and stranded wires **without** ferrules

Part No.	with crimp connection
	Wire mm ²
	fine-stranded 0.75 – 4.0 ²⁾
	Term. poles 1
	Thread M20 x 1.5
	Gland inside
96.134.2053.0	
96.134.2053.1	

Contacts separately under Accessories