

**Passeinsatz für Einsätze E14 4 A  
COMBI CHECK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



The main function of the voltage tester is to establish if voltage is present. A 2-pole voltage tester is the only approved testing instrument that fulfils the requirements of work protection regulations.

- with LED-Display
- acc. to VDE standard
- high peak voltage strength
- the right tester for every application

**General ordering data**

|            |   |
|------------|---|
| Type       | COMBI CHECK                                       |
| Order No.  | <a href="#">9918860000</a>                        |
| Version    | 2-pole voltage tester type 1156, *UNDEFINED TEXT* |
| GTIN (EAN) | 4032248405749                                     |
| Qty.       | 1 pc(s).  |

**Passeinsatz für Einsätze E14 4 A  
COMBI CHECK**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technische Daten**

**Dimensions and weights**

|        |       |            |       |
|--------|-------|------------|-------|
| Weight | 290 g | Net weight | 290 g |
|--------|-------|------------|-------|

**Product data**

|                       |                                    |                            |                                    |
|-----------------------|------------------------------------|----------------------------|------------------------------------|
| Rated voltage, min.   | 6 V                                | AC voltage measuring range | 6-690 V                            |
| Frequency range, min. | 0 Hz                               | Frequency range, max.      | 100 Hz                             |
| Rated voltage, max.   | 690 V AC/DC                        | Protection degree          | IP 65                              |
| Battery type          | 1.5 V type AAA battery             | Peak voltage resistance    | 8 kV                               |
| Display               | LED                                | DC voltage display         | 6,12, 24, 50, 120, 230, 400, 690 V |
| AC voltage display    | 6,12, 24, 50, 120, 230, 400, 690 V |                            |                                    |

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000494    | UNSPSC     | 41-11-36-37 |
| eClass 5.1 | 27-20-03-08 | eClass 6.2 | 27-20-03-08 |
| eClass 7.1 | 27-20-03-08 |            |             |

**Product information**

|                                 |                  |
|---------------------------------|------------------|
| Descriptive text technical data | Inklusive Buzzer |
|---------------------------------|------------------|

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Passeinsatz für Einsätze E14 4 A  
COMBI CHECK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Zeichnungen**

