

**Conductor markers
VT SF 2/21 MC NE WS V0**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



SlimFix are conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. They consist of halogen-free material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm²
- Markers in proven MultiCard format

General ordering data

| | |
|------------|--|
| Type | VT SF 2/21 MC NE WS V0 |
| Order No. | 1689410001 |
| Version | Conductor markers, MultiCard, 21 x 3.6 mm, Polyamide 66, Colour: White |
| GTIN (EAN) | 4008190872342 |
| Qty. | 800 pc(s). |

**Conductor markers
VT SF 2/21 MC NE WS VO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten
Dimensions and weights

| | | | |
|------------|---------|-------|--------|
| Length | 21 mm | Width | 3.6 mm |
| Height | 3.65 mm | Depth | 3.5 mm |
| Net weight | 0.228 g | | |

General data

| | | | |
|--|--------|-----------------------------------|--------------|
| Colour | White | Material | Polyamide 66 |
| Material colour according to resistance code | 9 | Operating temperature range, max. | 120 °C |
| Operating temperature range, min. | -50 °C | Size of labelling field | 21x3.6 mm |
| Type of printing | blank | UL 94 flammability rating | V-0 |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|-------------------------------|----------------------|
| Conductor O.D., max. | 2.9 mm | Conductor O.D., min. | 2.2 mm |
| Conductor cross-section, max. | 1.5 mm ² | Conductor cross-section, min. | 0.75 mm ² |
| Halogen | No | | |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001530 | UNSPSC | 44-12-17-08 |
| eClass 5.1 | 27-14-91-03 | eClass 6.2 | 27-14-91-03 |
| eClass 7.1 | 27-14-91-03 | | |

Approvals

| | |
|-----------|---------|
| Approvals | |
| ROHS | Conform |

Downloads

| | |
|---|------------------------------------|
| M-Print [®] PRO configuration file | mc_sf_2_21_mcf.zip |
|---|------------------------------------|