

## SAISW-5/7

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems. The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

### General ordering data

Type	SAISW-5/7
Order No.	<a href="#">9456950000</a>
Version	Sockets prefabricated to customer spec., Plugs prefabricated to customer spec., M12, pin, 90°
GTIN (EAN)	4008190304003
Qty.	1 pc(s).

## SAISW-5/7

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Net weight 25 g

### Technical data customisable plug-in connectors

Cable diameter	4...6 mm (PG7)/ 6...8 mm (PG9)	Cable diameter, max.	6 mm
Cable diameter, min.	4 mm	Cable gland	PG 7
Coding	A	Connection cross-section, max.	0.75 mm <sup>2</sup>
Connection cross-section, min.	0.14 mm <sup>2</sup>	Contact surface	CuSnZn
Housing main material	PA	Insulation resistance	10 <sup>8</sup> Ω
No. of poles	5	Plugging cycles	500
Pollution severity	3	Protection degree	IP 67
Rated current	4 A	Rated voltage	125 V
Rated voltage (text)	125 V (5-pole) / 60 V (8-pole)	Shield connection	No
Threaded ring material	Diecast zinc	Type of connection	Screw connection

### Classifications

ETIM 3.0	EC002062	UNSPSC	30-21-18-10
eClass 5.1	27-26-07-01	eClass 6.2	27-26-07-02
eClass 7.1	27-44-01-02		

### Approvals

Approvals



ROHS Conform