

**Multipin terminal strip  
D4 KS4 TP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



D 4 ( für KS4 ) 014050



Multi-pole terminal strips have been part of the Weidmüller portfolio for many years. The terminal rails can be screwed directly to the housing. A retightening of the clamping screw when setting the wire is not needed with these terminals. The terminal strips are available in the materials KRG and PA and with different connection systems.

**General ordering data**

Type	D4 KS4 TP
Order No.	<a href="#">014050000</a>
Version	Multipin terminal strip, Single- and multi-pole terminal strip, Rated cross-section: Screw connection, Direct mounting
GTIN (EAN)	4008190095574
Qty.	50 pc(s).

**Multipin terminal strip  
D4 KS4 TP**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technische Daten**

**Dimensions and weights**

Length	6,600 mm	Width	48 mm
Height	6.8 mm	Height of lowest version	6.8 mm
Net weight	3.2 g		

**Temperatures**

Operating temperature		Storage temperature	
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C

**Additional technical data**

Explosion-tested version	No	Installation advice	Direct mounting
Type of mounting	Direct mounting	Version	For the mounting rails

**Clampable wires (rated connection)**

Type of connection	Screw connection	Connection direction	on side
--------------------	------------------	----------------------	---------

**Material data**

Material	PA 66	Colour	Transparent
UL 94 flammability rating	V-2		

**System specifications**

Product family	Multipin terminal strip	Type of connection	Screw connection
Connection direction	on side	End cover plate required	No

**Classifications**

ETIM 3.0	EC001284	UNSPSC	30-21-18-11
eClass 5.1	27-14-11-06	eClass 6.2	27-14-92-14
eClass 7.1	27-14-92-14		

**Approvals**

Approvals



ROHS	Conform
------	---------