

## HDC enclosures HDC 04A TOLU 1M20G

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

### General ordering data

Type	HDC 04A TOLU 1M20G
Order No.	<a href="#">1788820000</a>
Version	HDC enclosures, Size: 1, Protection degree: IP 65, Cable entry from top, Plug housing. Side-locking clamp on lower side, Standard, Size of cable entries: M 20
GTIN (EAN)	4032248206360
Qty.	1 pc(s).

## HDC enclosures HDC 04A TOLU 1M20G

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Length	26.8 mm	Width	36.5 mm
Height	50 mm	Net weight	26 g

### Dimensions

Total length housing	26.8 mm	Width housing C	26.8 mm
Height of housing B	50 mm	Cable entry	w. threading

### General data

Housing main material	diecast aluminium
-----------------------	-------------------

### Version

Internal thread	M 20	Design of housing	Cable entry from top, Plug housing
Size	1	Design	Standard
Top part/bottom part/lid	upper part	Design of locking system	Side-locking clamp on lower side
Cable entry	w. threading	Size of cable entries	M 20
Number of cable entry on top	1	Number of cable entry sideways	0

### Classifications

ETIM 3.0	EC000437	UNSPSC	30-21-18-01
eClass 5.1	27-14-34-19	eClass 6.2	27-26-12-03
eClass 7.1	27-44-02-02		

### Approvals

Approvals



ROHS	Conform
------	---------

### Downloads

PDF	<a href="#">1788820000_HDC_04A_TOLU_1M20G_STP_Blatt__1.pdf</a>
IGES	<a href="#">1788820000_HDC_04A_TOLU_1M20G_STP.igs</a>
VRML	<a href="#">1788820000_HDC_04A_TOLU_1M20G_STP.wrl</a>
EPLAN	<a href="#">1788820000.MZF</a>
<a href="#">3D Modell</a>	

**Datenblatt**

**HDC enclosures  
HDC 04A TOLU 1M20G**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Zeichnungen**

