

**HDC enclosures  
HDC 06B SDLU 2PG16G**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

**General ordering data**

Type	HDC 06B SDLU 2PG16G
Order No.	<a href="#">1652990000</a>
Version	HDC enclosures, Size: 3, Protection degree: IP 65, Base enclosure, End-locking clamp, lower side, Standard, with cover, Size of cable entries: PG 16
GTIN (EAN)	4008190403065
Qty.	1 pc(s).

## HDC enclosures HDC 06B SDLU 2PG16G

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Length	82 mm	Width	92.5 mm
Height	72 mm	Mounting dimension - width	70 mm
Mounting dimension - height	40 mm	Net weight	285 g

### Dimensions

Total length housing	60 mm	Width housing C	43 mm
Width base C1	54.5 mm	Height of housing B	72 mm
Height of base B1	5 mm	Hole pitch length A2	70 mm
Cable entry	w. threading		

### General data

Protection class note	Protection class with secured cover: IP 65	Housing main material	diecast aluminium
-----------------------	--	-----------------------	-------------------

### Version

Internal thread	PG 16	Design of housing	Base enclosure
Size	3	Design	Standard
Top part/bottom part/lid	lower part	Design of locking system	End-locking clamp, lower side
Cable entry	w. threading	Size of cable entries	PG 16
Number of cable entry on top	0	Number of cable entry sideways	2
Cover	with cover	Design of cover	with cover

### Classifications

ETIM 3.0	EC000437	UNSPSC	30-21-18-01
eClass 5.1	27-14-34-19	eClass 6.2	27-26-12-03
eClass 7.1	27-44-02-02		

### Approvals

Approvals



ROHS	Conform
------	---------

### Downloads

PDF	<a href="#">1652990000_HDC_06B_SDLU_2PG16G_STP_Blatt_1.pdf</a>
IGES	<a href="#">1652990000_HDC_06B_SDLU_2PG16G_STP.igs</a>
VRML	<a href="#">1652990000_HDC_06B_SDLU_2PG16G_STP.wrl</a>
EPLAN	<a href="#">1652990000.MZF</a>
<a href="#">3D Modell</a>	

**HDC enclosures  
HDC 06B SDLU 2PG16G**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Zeichnungen**