

**SAK Series  
SAKG 32 II/GW**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



The Weidmüller SAKG range includes the following connection types:

- Combined clamping yoke/flat-blade connection, version I
- Flat spade connection, version II.

Here, two types of cable glands are intended:

- a) screw set with lock nut
- b) with threads on the busbar clamping yoke connection, version III.

The stripped conductor can be connected without any further preparation.

**General ordering data**

Type	SAKG 32 II/GW
Order No.	<a href="#">0185120000</a>
Version	SAK Series, Feed-through terminal, Rated cross-section: 50 mm <sup>2</sup> , Screw connection, Medium Yellow
GTIN (EAN)	4008190014568
Qty.	10 pc(s).

## SAK Series SAKG 32 II/GW

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Length	80 mm	Width	32 mm
Height	53 mm	Height of lowest version	53 mm
Weight	146 g	Net weight	138.7 g

### Temperatures

Operating temperature		Storage temperature	
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

### Additional technical data

Explosion-tested version	No	Number of similar terminals	1
Open sides	Open	Type of mounting	Snap-on
Version	Stud terminal		

### CSA ratings data

Certificate No. (CSA)	12400-199	Voltage size C (CSA)	600 V
Current size C (CSA)	170 A	Wire cross section max. (CSA)	00 AWG
Wire cross section min. (CSA)	1 AWG		

### Clampable wires (rated connection)

Type of connection	Screw connection	Connection direction	on side
Number of connections	1	Clamping range, rated connection, min.	10 mm <sup>2</sup>
Clamping range, rated connection, max.	70 mm <sup>2</sup>	Clamping screw	M 8
Tightening torque, min.	6 Nm	Tightening torque, max.	12 Nm
Wire connection cross section AWG, min.	AWG 1	Wire connection cross section AWG, max.	AWG 2/0

### Rated data

Rated cross-section	50 mm <sup>2</sup>	Rated voltage	1,000 V
Rated impulse withstand voltage	8 kV	Rated current	150 A
Current at maximum wires	192 A	Standards	IEC 60947-7-1
Pollution severity	3		

### Material data

Material	KrG	Colour	Medium Yellow
UL 94 flammability rating	V-0, 5VA		

### System specifications

Product family	SAK Series	Type of connection	Screw connection
Connection direction	on side	Number of levels	1
Number of connections	1	No. of clamping points per level	2
Levels cross-connected internally	No	Mounting rail	TS 32
End cover plate required	Yes		

**SAK Series  
SAKG 32 II/GW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technische Daten**

**Classifications**

ETIM 3.0	EC000897	UNSPSC	30-21-18-11
eClass 5.1	27-14-11-31	eClass 6.2	27-14-11-20
eClass 7.1	27-14-11-20		

**Product information**

Descriptive text technical data      Conductor connection with cable lugs according to DIN 46234 and DIN 46235, from 10 .. 70 mm<sup>2</sup>

**Approvals**

Approvals



ROHS      Conform

**Downloads**

DXF	<a href="#">01427_SAKG_32_II-GW_DXF.dxf</a>
STEP	<a href="#">0185120000_01427_SAKG_32_II-GW_STP.stp</a>