

SAK Series SAKG 32/35 II

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



In order to do justice to the different requirements placed on our products, it is necessary to use various insulating materials tailored to the particular application. None of the insulating materials used by Weidmüller contain any hazardous substances. Above all, we ensure that all our materials are free from cadmium. Furthermore, they contain no colour pigments based on heavy metals and do not lead to the formation of dioxin/furan.

General ordering data

Type	SAKG 32/35 II
Order No.	0637320000
Version	SAK Series, Feed-through terminal, Rated cross-section: 50 mm ² , Screw connection, Medium Yellow
GTIN (EAN)	4008190018276
Qty.	10 pc(s).

SAK Series SAKG 32/35 II

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

Length	80 mm	Width	32 mm
Height	53 mm	Height of lowest version	53 mm
Net weight	158.4 g		

Temperatures

Operating temperature		Storage temperature	
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

Additional technical data

Explosion-tested version	No	Number of similar terminals	1
Open sides	Open	Type of mounting	Snap-on
Version	Stud terminal		

CSA ratings data

Certificate No. (CSA)	12400-199	Voltage size C (CSA)	600 V
Current size C (CSA)	170 A	Wire cross section max. (CSA)	00 AWG
Wire cross section min. (CSA)	1 AWG		

Clampable wires (rated connection)

Type of connection	Screw connection	Connection direction	on side
Number of connections	1	Clamping range, rated connection, min.	10 mm ²
Clamping range, rated connection, max.	70 mm ²	Clamping screw	M 8
Tightening torque, min.	6 Nm	Tightening torque, max.	12 Nm
Wire connection cross section AWG, min.	AWG 6	Wire connection cross section AWG, max.	AWG 3/0

Rated data

Rated cross-section	50 mm ²	Rated voltage	1,000 V
Rated impulse withstand voltage	8 kV	Rated current	150 A
Current at maximum wires	192 A	Standards	IEC 60947-7-1
Pollution severity	3		

UL ratings data

Certificate No. (UR)	E60693	Voltage size C (UR)	600 V
Current size C (UR)	200 A	Conductor size Factory wiring max. (UR)	000 AWG
Conductor size Factory wiring min. (UR)	6 AWG	Conductor size Field wiring max. (UR)	000 AWG

Material data

Material	KrG	Colour	Medium Yellow
UL 94 flammability rating	V-0, 5VA		

Datenblatt

**SAK Series
SAKG 32/35 II**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

System specifications

Product family	SAK Series	Type of connection	Screw connection
Connection direction	on side	Number of levels	1
Number of connections	1	No. of clamping points per level	2
Levels cross-connected internally	No	Mounting rail	TS 35
End cover plate required	Yes		

Classifications

ETIM 3.0	EC000897	UNSPSC	30-21-18-11
eClass 5.1	27-14-11-31	eClass 6.2	27-14-11-20
eClass 7.1	27-14-11-20		

Product information

Descriptive text technical data	Conductor connection with cable lugs according to DIN 46234 and DIN 46235, from 10 .. 70 mm ²
---------------------------------	--

Approvals

Approvals



ROHS	Conform
------	---------