

CABTITE KT 8**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

General ordering data

Type	CABTITE KT 8
Order No.	1826510000
Version	Cable grommet, Plastic
GTIN (EAN)	4032248329335
Qty.	10 pc(s).

CABTITE KT 8

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technische Daten**Dimensions and weights**

Net weight	8.1 g
------------	-------

General information

Clamping range, max.	9 mm	Clamping range, min.	8 mm
Material	Plastic	Operating temperature range, max.	80 °C
Operating temperature range, min.	-20 °C		

Classifications

ETIM 3.0	EC000441	UNSPSC	30-21-18-01
eClass 5.1	27-14-92-01	eClass 6.2	27-14-92-01
eClass 7.1	27-14-92-01		

Approvals

Approvals	
ROHS	Conform