

**CABTITE KT 8 b**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

**General ordering data**

Type	CABTITE KT 8 b
Order No.	<a href="#">1827850000</a>
Version	Cable grommet, Plastic
GTIN (EAN)	4032248333165
Qty.	10 pc(s).

**CABTITE KT 8 b**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technische Daten****Dimensions and weights**

Net weight	6.2 g
------------	-------

**General information**

Clamping range, max.	9 mm	Clamping range, min.	8 mm
Material	Plastic	Operating temperature range, max.	80 °C
Operating temperature range, min.	-20 °C		

**Classifications**

ETIM 3.0	EC000441	UNSPSC	30-21-18-01
eClass 5.1	27-14-92-01	eClass 6.2	27-14-92-01
eClass 7.1	27-14-92-01		

**Approvals**

Approvals	
ROHS	Conform