

CABTITE KT 2/4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

General ordering data

| | |
|------------|----------------------------|
| Type | CABTITE KT 2/4 |
| Order No. | 1826620000 |
| Version | Cable grommet, Plastic |
| GTIN (EAN) | 4032248329441 |
| Qty. | 10 pc(s). |

CABTITE KT 2/4

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technische Daten**Dimensions and weights**

| | |
|------------|-------|
| Net weight | 8.5 g |
|------------|-------|

General information

| | | | |
|-----------------------------------|---------|-----------------------------------|-------|
| Clamping range, max. | 4 mm | Clamping range, min. | 4 mm |
| Material | Plastic | Operating temperature range, max. | 80 °C |
| Operating temperature range, min. | -20 °C | | |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000441 | UNSPSC | 30-21-18-01 |
| eClass 5.1 | 27-14-92-01 | eClass 6.2 | 27-14-92-01 |
| eClass 7.1 | 27-14-92-01 | | |

Approvals

| | |
|-----------|---------|
| Approvals | |
| ROHS | Conform |