

CABTITE KVT 25**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

General ordering data

Type	CABTITE KVT 25
Order No.	1826660000
Version	Cable entry strips, Plastic
GTIN (EAN)	4032248329489
Qty.	10 pc(s).

CABTITE KVT 25

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technische Daten**Dimensions and weights**

Net weight 16.15 g

General information

Clamping range, max.	0 mm	Clamping range, min.	0 mm
Material	Plastic	Operating temperature range, max.	70 °C
Operating temperature range, min.	-5 °C		

Classifications

ETIM 3.0	EC000441	UNSPSC	30-21-18-01
eClass 5.1	27-14-92-01	eClass 6.2	27-14-92-01
eClass 7.1	27-14-92-01		

Product information

Descriptive text ordering data The splittable cable glands are supplied without locknut; this has to be ordered separately.

Approvals

Approvals
ROHS Conform

Downloads

STEP [1826660000_XXXXX_KVT_25_Cabtite_STP.stp](#)