

**CABTITE KVT 32****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Cabtite enables you to feed pre-assembled lines through the electrical cabinet wall while maintaining IP54-level protection. As the cable does not have to be split, the manufacturer's guarantee is not invalidated.

**General ordering data**

Type	CABTITE KVT 32
Order No.	<a href="#">1826670000</a>
Version	Cable entry strips, Plastic
GTIN (EAN)	4032248329496
Qty.	10 pc(s).

**CABTITE KVT 32**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technische Daten****Dimensions and weights**

Net weight 16 g

**General information**

Clamping range, max.	0 mm	Clamping range, min.	0 mm
Material	Plastic	Operating temperature range, max.	70 °C
Operating temperature range, min.	-5 °C		

**Classifications**

ETIM 3.0	EC000441	UNSPSC	30-21-18-01
eClass 5.1	27-14-92-01	eClass 6.2	27-14-92-01
eClass 7.1	27-14-92-01		

**Product information**

Descriptive text ordering data The splittable cable glands are supplied without locknut; this has to be ordered separately.

**Approvals**

Approvals  
ROHS Conform

**Downloads**

STEP [1826670000\\_XXXXX\\_KVT\\_32\\_Cabtite\\_STP.stp](#)