

**Bolt-type screw terminals, Accessories  
WAH 185/300 BE**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



The comprehensive range of bolt-type screw terminals offers secure connections for all power transmission applications.

Connections from 10 mm<sup>2</sup> to 300 mm<sup>2</sup> are possible. The conductors are attached to the terminals using crimped cable lugs and each connection secured by tightening the hexagonal nut.

Bolt-type screw terminals with threads from M5 to M16 can be used depending on the conductor cross-section. A low voltage drop and the use of a self-extinguishing material with a V-0 (UL 94) flammability rating guarantee maximum safety.

All bolt-type screw terminals have been tested according to international railway standards (EN 50343, EN 50155, NF F61-017, NF16-101; Ria 20) and comply with the requirements of those standards.

**General ordering data**

Type	WAH 185/300 BE
Order No.	<a href="#">1064760000</a>
Version	Bolt-type screw terminals, Accessories, Hood, Beige, 54 mm
GTIN (EAN)	4008190108267
Qty.	10 pc(s).

## Bolt-type screw terminals, Accessories WAH 185/300 BE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Length	139 mm	Width	54 mm
Height	43.9 mm	Net weight	25.5 g

### Temperatures

Operating temperature		Storage temperature	
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C

### Additional technical data

Explosion-tested version	No	Installation advice	Direct mounting
--------------------------	----	---------------------	-----------------

### Material data

Material	Polyamide 66	Colour	Beige
UL 94 flammability rating	V-2		

### System specifications

Product family	Bolt-type screw terminals, Accessories
----------------	---

### Classifications

ETIM 3.0	EC000886	UNSPSC	30-21-18-27
eClass 5.1	27-14-11-33	eClass 6.2	27-37-12-06
eClass 7.1	27-37-12-06		

### Approvals

ROHS	Conform
------	---------