

PB-DP SUB-D M12 TERM PS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

General ordering data

Type	PB-DP SUB-D M12 TERM PS
Order No.	1140640000
Version	
GTIN (EAN)	4032248922611
Qty.	1 pc(s).

PB-DP SUB-D M12 TERM PS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

Net weight 71.8 g

Technical specifications for sub-D connector

Data rate	12 Mbit/s	Housing main material	ZnAl
Humidity	Max. 75% at +25°C, non-condensing	Interlock	UNC4-40
Outgoing elbow	90°	PROFIBUS DP PG interface	D-Sub 9-pole, Socket
PROFIBUS DP interface		PROFIBUS cable interface	M12 B-coded male and female connector, pins 2 and 4 assigned
Plug-in connector and pin assignment	D-Sub 9-pole, Pin In accordance with the PROFIBUS specification	Plugging cycles	≥ 200
Protection degree	IP 30	Temperature range of housing	-20...+70 ° C

Classifications

eClass 6.2	27-26-07-07	eClass 7.1	27-44-03-07
------------	-------------	------------	-------------

Approvals

ROHS	Conform
------	---------