

**MCZ SERIES**  
**MCZ PT100/3 CLP 0...100C**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



Output-current loop-powered PT100 signal converters in 3 designs

The signal converters designed for a specific temperature range are suitable for connecting 2- and 3-conductor PT100 sensors. On the output side there is a loop-powered 4...20 mA signal.

I.e. the active analogue control interface powers the signal converter.

The signal converters can be mounted on a TS35 rail and feature high accuracy and linearity.

**General ordering data**

Type	MCZ PT100/3 CLP 0...100C
Order No.	<a href="#">8425720000</a>
Version	MCZ SERIES, RTD transformer
GTIN (EAN)	4032248012664
Qty.	10 pc(s).

## MCZ SERIES MCZ PT100/3 CLP 0...100C

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technische Daten

### Dimensions and weights

Length	91 mm	Width	6 mm
Depth	63.2 mm	Net weight	29.8 g

### Temperatures

Operating temperature	-25 °C...+50 °C	Storage temperature	-25 °C...+85 °C
-----------------------	-----------------	---------------------	-----------------

### Probability of failure

MTTF	1,066 Years
------	-------------

### Input

Sensor supply	0.8 mA / 9...30 V DC	Supply voltage	max. 30 V/ min. 9 V + (20 mA x RL)
Number of inputs	1	Temperature input range	0...100 °C
Sensor	PT100/2-/3-wire (in compliance with IEC 751)		

### Output

Number of outputs	1	load impedance current	≤ 600 Ω
Output current	4...20 mA (current loop)		

### General data

Accuracy	Typical 0.2%, max. 0.5% of FSR	Configuration	none
Galvanic isolation	Without isolation	Input/Output	PT100/ 4...20 mA (current loop)
Linearity	Yes	Mounting rail	TS 35
Step response time	10 ms	Supply voltage	max. 30 V/ min. 9 V + (20 mA x RL)
Temperature coefficient	max. ± 250 ppm/K	Type of connection	Tension clamp connection

### Insulation coordination

EMC standards	EN 61000-6	Galvanic isolation	Without isolation
Standards	DIN EN 50178, DIN EN 61000-4-2		

### Classifications

ETIM 3.0	EC001774	UNSPSC	30-21-18-01
eClass 5.1	27-20-02-06	eClass 6.2	27-20-02-06
eClass 7.1	27-20-02-06		

### Product information

Descriptive text ordering data	
Descriptive text accessories	Cross-connectors for power supplies and markers: refer to accessories

**Datenblatt****MCZ SERIES**  
**MCZ PT100/3 CLP 0...100C****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com**Technische Daten****Approvals**

Approvals



ROHS

Conform

**Downloads**

Package insert

[instruction sheet.pdf](#)

Declaration of Conformity

[Declaration of Conformity.pdf](#)[3D Modell](#)




**Datenblatt**

**MCZ SERIES  
MCZ PT100/3 CLP 0...100C**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Zeichnungen**

**Electric symbol**



dimensions