

## Terminal markers DEK 5/6 MC NE WS

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Connector markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

### General ordering data

|            |  |
|------------|--|
| Type       | DEK 5/6 MC NE WS   |
| Order No.  | <a href="#">1609820000</a>   |
| Version    | Terminal markers, MultiCard, 5 x 6 mm, Polyamide 66, Colour: White |
| GTIN (EAN) | 4008190203436  |
| Qty.       | 1,000 pc(s).   |

## Terminal markers DEK 5/6 MC NE WS

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

|            |        |       |      |
|------------|--------|-------|------|
| Length     | 5 mm   | Width | 6 mm |
| Net weight | 0.13 g |       |      |

### General data

|  |        |                                   |              |
|--|--------|-----------------------------------|--------------|
| Colour                                       | White  | Material                          | Polyamide 66 |
| Material colour according to resistance code | 9      | Operating temperature range, max. | 100 °C       |
| Operating temperature range, min.            | -40 °C | UL 94 flammability rating         | V-2          |

### Connector markers

|                 |      |
|-----------------|------|
| Pitch in mm (P) | 6 mm |
|-----------------|------|

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000761    | UNSPSC     | 30-21-18-07 |
| eClass 5.1 | 27-14-11-37 | eClass 6.2 | 27-14-11-37 |
| eClass 7.1 | 27-14-11-37 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                                 |   |
|---------------------------------|---|
| M-Print® PRO configuration file | <a href="#">mc_dek_5_6_mcf.zip</a>                  |
| DXF                             | <a href="#">20841_DEK_5-6_MC_DXF.dxf</a>            |
| STEP                            | <a href="#">1609820000_20841_Dek_5x6_MC_STP.stp</a> |

**Datenblatt**

**Terminal markers  
DEK 5/6 MC NE WS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Zeichnungen**

**Example of use**



**Drawing**

