

SAIL-VSA-M12G-1.5U

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Weidmüller can supply valve plugs as connecting lines with M12 plugs and one end without connector. The status of the valve plug is shown by an LED. Every valve plug is fitted with a protective circuit. The Weidmüller range includes valve plugs of type A, B and C to DIN and industry standards. In the plugged condition they achieve IP 67 class of protection. The outlet direction is also a decisive factor: Weidmüller can also supply 0° versions, i.e. the cable outlet direction is located at the PE contact.

General ordering data

| | |
|------------|---|
| Type | SAIL-VSA-M12G-1.5U |
| Order No. | 9457040000 |
| Version | Valve plug, Straight plug - valve plug, A |
| GTIN (EAN) | 4008190311032 |
| Qty. | 1 pc(s). |

SAIL-VSA-M12G-1.5U

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

| | |
|------------|-------|
| Net weight | 121 g |
|------------|-------|

Technical specifications for cable

| | | | |
|--------------------|---------------------|------------------|-------|
| Core cross-section | 0.5 mm ² | shielded | No |
| Sheath material | PUR | Sheathing colour | Black |
| Cable length | 1.5 m | Halogen | No |

General technical data

| | | | |
|------------------------------|----------------------------|-----------------------|-------------------------|
| Version | Straight plug - valve plug | Contact tube diameter | Miscellaneous |
| Coding | Design A (18 mm), M12 = A | Protection degree | IP 67 (when screwed in) |
| Contact surface | tinned | LED | Yes |
| Rated voltage | 24 V | Rated current | 4 A |
| Temperature range of housing | -25...+80 °C | | |

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC001855 | UNSPSC | 30-21-18-10 |
| eClass 5.1 | 27-26-07-01 | eClass 6.2 | 27-27-92-18 |
| eClass 7.1 | 27-06-91-90 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|