


**W-Series
WDU 70/95**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The versatile and extensive range of products - from 0.05 mm² to 300 mm² - means that you have diverse options for your applications at your disposal. Hardened steel for mechanical strength and high-quality tinned copper for optimum conductivity. All materials comply with RoHS requirements and have been tested to current environment guidelines.

General ordering data

Type	WDU 70/95
Order No.	102460000
Version	W-Series, Feed-through terminal, Rated cross-section: 95 mm ² , Screw connection, Direct mounting
GTIN (EAN)	4008190105990
Qty.	10 pc(s).

W-Series WDU 70/95

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Dimensions and weights

Length	132 mm	Width	27 mm
Height	107 mm	Height of lowest version	115.5 mm
Weight	340 g	Net weight	330.89 g

Temperatures

Operating temperature		Storage temperature	
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C

Rated data IECEx/ATEX

Certificate No. (ATEX)	KEMA98ATEX1686U	ATEX certificate	KEMA98ATEX1686U_d.pdf
ATEX certificate	KEMA98ATEX1686U_e.pdf	Max. voltage (ATEX)	690 V
Current (ATEX)	202 A	Wire cross section max. (ATEX)	70 mm ²
Voltage, cross-connection		Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity
	CrossConnectionGuide.pdf		
Marking EN 60079-7	Ex e II	Marking ATEX Directive 94/9/EC	II 2 G D

2 clampable wires (H05V/H07V) same cross-section (rated connection)

Cross-section for connected wire, stranded, two clampable wires, min.	16 mm ²	Cross-section for connected wire, stranded, two clampable wires, max.	35 mm ²
Wire connection cross section, finely stranded, two clampable wires, min.	16 mm ²	Wire cross-section, finely stranded, two clampable wires, max.	35 mm ²
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, min.	16 mm ²	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, max.	35 mm ²

Additional technical data

Explosion-tested version	Yes	Installation advice	Direct mounting
Number of similar terminals	1	Open sides	closed
Type of mounting	Snap-on	Version	Screw connection, for screwable cross-connection, closed

CSA ratings data

Certificate No. (CSA)	12400-242	Voltage size B (CSA)	600 V
Voltage size C (CSA)	600 V	Voltage size D (CSA)	600 V
Current size B (CSA)	205 A	Current size C (CSA)	205 A
Current size D (CSA)	5 A	Wire cross section max. (CSA)	00 AWG
Wire cross section min. (CSA)	6 AWG		

W-Series WDU 70/95

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Clampable wires (rated connection)

Type of connection	Screw connection	Stripping length	30 mm
Blade size	S6 (DIN 6911)	Connection direction	on side
Number of connections	2	Clamping range, rated connection, min.	13.3 mm ²
Clamping range, rated connection, max.	120 mm ²	Clamping screw	M 8
Tightening torque, min.	6 Nm	Tightening torque, max.	12 Nm
Gauge to IEC 60947-1	B12	Wire connection cross section, solid core, max. rated connection	16 mm ²
Wire connection cross section, solid core max. rated connection	16 mm ²	Wire connection cross section, stranded, rated connection, min.	16 mm ²
Wire connection cross section, stranded, rated connection, max.	120 mm ²	Wire connection cross section, finely stranded, max.	95 mm ²
Wire connection cross-section, finely stranded, min.	16 mm ²	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min.	16 mm ²
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max.	95 mm ²	Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min.	16 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max.	50 mm ²	Wire connection cross section AWG, min.	AWG 6
Wire connection cross section AWG, max.	AWG 2/0		

Rated data

Rated cross-section	95 mm ²	Rated voltage	1,000 V
Rated impulse withstand voltage	8 kV	Rated current	232 A
Current at maximum wires	232 A	Standards	IEC 60947-7-1
Pollution severity	3		

Strap connection

Band 1, No. of layers, min.	4: 16 x 0.8	Band 1, No. of layers, max.	1 x 10: 16 x 0.8
Band 2, No. of layers, min.	3: 9 x 0.8	Band 2, No. of layers, max.	6: 9 x 0.8

UL ratings data

Certificate No. (UR)	E60693	Voltage size C (UR)	1000 V
Current size C (UR)	175 A	Conductor size Factory wiring max. (UR)	00 AWG
Conductor size Factory wiring min. (UR)	6 AWG	Conductor size Field wiring max. (UR)	00 AWG

Material data

Material	Wemid	Colour	Dark Beige
UL 94 flammability rating	V-0		

System specifications

Product family	W-Series	Type of connection	Screw connection
Connection direction	on side	Number of levels	1
Number of connections	2	No. of clamping points per level	2
Levels cross-connected internally	No	Mounting rail	TS 35
End cover plate required	No		

Datenblatt

**W-Series
WDU 70/95**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Classifications

ETIM 3.0	EC000897	UNSPSC	30-21-18-11
eClass 5.1	27-14-11-20	eClass 6.2	27-14-11-20
eClass 7.1	27-14-11-20		

Product information

Descriptive text ordering data	For details on ribbon cable, see our online catalogue and for information on direct mounting, see section on W-series Accessories.
Descriptive text accessories	Auxiliary connection for the additional conductor "WZAD 70", order No. 1066000000 (up to 4 mm², 32 A)

Approvals

Approvals



ROHS Conform

Datenblatt

W-Series
WDU 70/95

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Zeichnungen

