

# CAGE CLAMP® S Rail-Mounted Terminal Blocks 2000 to 2016 Series

## Simply push-in




Directly insert solid and ferruled conductors.

## Conductor termination



Terminating fine-stranded conductors using an operating tool.

## Insulation stop




Conductor termination – Insulation stop.

## Simply jumpered



Insert push-in type jumper bar and push down firmly until it hits the backstop.

## CAGE CLAMP®S for all conductor types



## Customizable push-in type jumper bars



Breaking off jumper contacts (up to 4 mm<sup>2</sup>/AWG 12)

## Customizable push-in type jumper bars




Marking with a felt-tip pen.

## Commoning with step-down jumpers



Commoning with step-down jumpers.

## Star point jumpers



Star point jumpers designed for 'Y' configuration

**CAGE CLAMP®S**  
clamps the following  
copper conductors:<sup>\*</sup>

solid


stranded

fine-stranded,  
also with tinned  
single strands

\* For aluminum conductors, see notes in Section 14.

## - Description and Handling -

### Simply smaller



Up to 30% more compact. Advantage: More wiring space or smaller switch cabinets/junction boxes.

### TOPJOB®S connectors



The 2001, 2002 and 2004 Series terminal blocks are equipped with a test socket for 2 mm Ø or 2.3 mm Ø test plugs.

### Testing tap



Testing tap suited for 2001 to 2016 Series terminal blocks. Tool-free connections for individual test wires up to 2.5 mm²/AWG 12.


### Test plug adapter



The test plug adapter for 4 mm Ø plugs is suited for 2001 to 2016 Series terminal blocks.




### Simply marked



Marker strips for center marking

### Wire jumpers



Push down the wire jumper until fully inserted.  
Lift the jumper with an operating tool for rewiring.

### Marking



WMB Inline  
WMB markers on roll

### Marking



TOPJOB®S group marker carrier, snap-on type for jumper slot

fine-stranded,  
tip-bonded

fine-stranded,  
with ferrule,  
(gaslight crimped)

fine-stranded,  
with pin terminal  
(gaslight crimped)