

# Rail-Mounted Terminal Blocks, Side-Entry 279 to 284 Series

## Assembly




Snapping side-entry rail-mounted terminal blocks onto the carrier rail.



Quick assembly keys prevent reverse mounting.

## Removal




Removal from the carrier rail.

## CAGE CLAMP® connection



Conductor termination



## Testing



Testing with test plug adapter.

## Commoning



Commoning with adjacent jumpers.



Commoning side-entry rail-mounted terminal blocks with step-down jumpers.

**CAGE CLAMP®**  
clamps the following  
copper conductors:<sup>\*</sup>

solid

stranded

fine-stranded,  
also with tinned  
single strands


\* For aluminum conductors, see notes in Section 14.

## – Description and Handling –





Suitable for all DIN 35 rails.

### Fuse terminal blocks



Replacing a fuse.

### Disconnect terminal blocks for test and measurement



### Marking



Marking with WMB Multi marking system.



fine-stranded,  
tip-bonded





fine-stranded,  
with ferrule ①  
(gastight crimped)



fine-stranded,  
with pin terminal  
(gastight crimped)

① When using ferruled conductors, it is necessary to use a terminal block one size larger than the nominal cross section of the wire.

<b>0.2 - 6 mm<sup>2</sup></b> 500 V/6 kV/3 ① I <sub>N</sub> 10 A	<b>AWG 24 - 10</b> 600 V, 10 A ④ 250 V, 10 A ⑤	<b>0.2 - 6 mm<sup>2</sup></b> 500 V/6 kV/3 ① I <sub>N</sub> 10 A	<b>AWG 24 - 10</b> 250 V, 10 A ⑥	<b>0.2 - 6 mm<sup>2</sup></b> 500 V/6 kV/3 ① I <sub>N</sub> 10 A	<b>AWG 24 - 10</b> 600 V, 10 A ④ 250 V, 10 A ⑤
Terminal block width 13 mm / 0.512 in  12 - 13 mm / 0.49 in ②			Terminal block width 13 mm / 0.512 in  12 - 13 mm / 0.49 in ②		



## Accessories for Fuse Terminal Blocks

Appropriate marking system:  
WMB (see Section 13)

<b>End and intermediate plate, 4 mm thick</b>	<b>Test plug adapter, 8.3 mm wide,</b>	
orange <b>282-312</b> 50 (2x25)	for terminal blocks 1.5 - 10 mm <sup>2</sup> , for test plug 4 mm Ø	
gray <b>282-311</b> 50 (2x25)	gray <b>209-170</b> 50 (2x25)	
<b>Adjacent jumper, insulated,</b>	<b>Test plug adapter, 6 mm wide,</b>	
I <sub>N</sub> 41 A gray <b>282-402</b> 100 (4x25)	with CAGE CLAMP®, for 0.08 - 2.5 mm <sup>2</sup> I <sub>N</sub> 24 A <b>281-407</b> 100 (4x25)	
<b>Protective warning marker,</b>	<b>Plunger,</b>	
with high-voltage symbol, black, for 5 terminal blocks yellow <b>282-405</b> 100 (4x25)	for 281, 282, 283 and 284 Series rail-mounted terminal blocks for side-entry <b>210-141</b>	1