


Female Connectors

Pin Spacing 5 mm, 5.08 mm MCS-MIDI Classic



- Universal connection for all conductor types
- Easy cable pre-assembly and on-unit wiring via vertical and horizontal CAGE CLAMP® actuation
- With coding fingers
- Integrated test ports

Technical data:	Straight female connectors:			Angled female connectors:		
	5 mm/5.08 mm 0.197 in/0.2 in			5 mm/5.08 mm 0.197 in/0.2 in		
Pin Spacing						
Rating per	IEC/EN 60664-1			IEC/EN 60664-1		
Overvoltage category	III	III	II	III	III	II
Pollution degree	3	2	2	3	2	2
Rated voltage	320 V	320 V	630 V	320 V	320 V	630 V
Rated surge voltage	4 kV	4 kV	4 kV	4 kV	4 kV	4 kV
Nominal current	16 A	16 A	16 A	14 A	14 A	14 A
Approvals per	UL/CSA			UL/CSA		
Use group UL 1059	B	C	D	B	C	D
Rated voltage	300 V	-	300 V	300 V	-	300 V
Nominal current UL	15 A	-	10 A	15 A	-	10 A
Nominal current CSA	15 A	-	10 A	15 A	-	10 A

The MCS-MIDI connection system is UL 1977 approved and capable of up to 600 V for factory wiring.


Conductor data:

Connection technology	CAGE CLAMP®		
Conductor size: solid	0.08 – 2.5 mm ²		
Conductor size: fine-stranded	0.08 – 2.5 mm ²		
Conductor size: fine-stranded	0.25 – 1.5 mm ² (with insulated ferrule)		
Conductor size: fine-stranded	0.25 – 2.5 mm ² (with uninsulated ferrule)		
AWG	28 – 12		
Strip length	8 – 9 mm / 0.31 – 0.35 in		

Material data:

Material group	I
Insulating material	Nylon 6.6 (PA 6.6)
Flammability rating per UL 94	V0
Lower/Upper temperature limit	-60°C / +85°C
Clamping spring material	Chrome-nickel spring steel (CrNi)
Contact material	Copper alloy
Contact plating	tin-plated

MCS connectors are also available upon request with gold-plated or partially gold-plated contact surfaces.
Depending on the version requested, "item no. suffix .../010-000" is added to the "basic item no."



MCS-MIDI accessories:

Marking accessories	540 – 543
Operating tools	466 – 467
Direct marking	358 – 360
Comb-style jumper bars	476
Insulation stop	469
Test plug adapter	474
Test plugs	538
Screws	546
Strain relief housings	472 – 473
Strain relief plates	470 – 471

MCS – MULTI CONNECTION SYSTEM includes connectors **without** breaking capacity in accordance with IEC 61984. When used as intended, these connectors shall not be connected/disconnected when live or under load. The circuit design should ensure header pins, which can be touched, are not live in unmated condition.