

WAGO Communication Cable



The WAGO communication cable offers a simple solution for communicating with the WAGO software tools (e.g., WAGO-I/O-CHECK, WAGO-I/O-PRO)

NOTICE: The communication cable must not be connected or removed when the system is energized.



The WAGO USB Service Cable connects a PC (notebook) to either the service Interface of the 857 Series Signal Conditioners and Relay Modules (JUMPFLEX) or to WAGO-I/O-SYSTEM buscouplers/controllers.

Notice:

Using the WAGO 759-923 USB Service Cable in combination with some of the programmable fieldbus controllers requires a certain firmware version or higher:

750-841 as from firmware version 1.2

750-872/0020-0000 as from firmware version 2

Description	Item No.	Pack. Unit
Communication cable (used to register or remove the end extension module)	750-920	10
Technical Data		
Ports	4-pole service connectors	
Length	2.5 m	
Operating temperature	0 °C ... +55 °C	
Degree of protection	IP20	
Weight	70 g	
Connector dimensions (WxHxD)	15 x 50 x 19 mm	

Description	Item No.	Pack. Unit
WAGO USB Communication Cable, length 2.5 m	750-923	1
WAGO USB Communication Cable, length 5 m	750-923/000-001	1
Technical Data		
USB specification	2.0 compatible/full-speed device	
Operating system	Microsoft® Windows® 2000; Microsoft® Windows® XP Professional; Microsoft® Windows® Vista®; Microsoft® Windows® 7	
Operating temperature	-25 °C ... +70 °C	
Interface USB	Type A/m	
Length	2.5 m (750-923) 5 m (750-923/000-001)	
Connector dimensions (WxHxD)	15 x 50 x 19	
Test voltage	2.5 kV, 50 Hz, 1 min.	
EMC: CE - immunity to interference	acc. to EN 61000-4-3, EN 61000-4-6	
EMC: CE - emission of interference	acc. to EN 55022	
Approvals		
Conformity marking	CE	