



	Interface module for ribbon cable connectors acc. to DIN 41651	Interface module for ribbon cable connectors acc. to DIN 41651
	Mounting carrier for DIN 35 rail	Mounting carrier for DIN 35 rail



Technical Data

Operating voltage	125 V AC / DC	125 V AC / DC
Nominal current	1 A	1 A
Connector contact	phosphor-bronze, 0.38 µm Au selectively over 1.3 µm Ni	phosphor-bronze, 0.38 µm Au selectively over 1.3 µm Ni
Performance level	3	3
Nominal voltage acc. to VDE 0110 Part 1/4.97, IEC 60664-1	125 V / 0.8 kV / 2	125 V / 0.8 kV / 2
Mounting direction	vertical	vertical
Ambient operating temperature	-20 °C ... +55 °C	-20 °C ... +55 °C
Storage temperature	-40 °C ... +70 °C	-40 °C ... +70 °C
Dimensions (mm) W x H x L incl. mounting feet or mounting carrier	W x 48 x 85	W x 62 x 85
Wire connection	Height from upper-edge of DIN 35 rail CAGE CLAMP® (WAGO 736 Series)	Height from upper-edge of DIN 35 rail CAGE CLAMP® (WAGO 737 Series)
Cross sections	0.08 mm² ... 2.5 mm² / AWG 28 ... 12	0.08 mm² ... 2.5 mm² / AWG 28 ... 12
Stripped lengths	5 ... 6 mm / 0.22 in	5 ... 6 mm / 0.22 in
Approvals	IEC 60603-1 / DIN 41651 Part 1 and 2	IEC 60603-1 / DIN 41651 Part 1 and 2
Accessories	see page 408	see page 408
WMB Multi marking system for mounting carrier	white 709-198 / transparent 709-197	white 709-198 / transparent 709-197
Marker strips for mounting carrier		