



HARTING PushPull Technology acc. to IEC 61 076-3-106 variant 4  
RJ45-panel feed-throughs and accessories

## Advantages

- Small, space-saving PushPull Interfaces in IP 65 / IP 67
- Easy handling of RJ45 patch cords in switch cabinets or sets
- Mounting to casings

## Technical characteristics

Locking	PushPull Technology acc. to IEC 61 076-3-106 variant 4
Transmission rate cat. 5 versions	10/100/1000 Mbit/s
Transmission rate cat. 6 versions	10/100 Mbit/s / 1/10 Gbit/s
Shielding	fully shielded, 360° shielding contact
Mating cycles	min. 750
Degree of protection	IP 65 / IP 67
Temperature range	-40 °C ... +70 °C
Housing material	Plastic, black Zinc die-cast, shining
Flammability acc. to UL 94	V0 UL approval (E102079)

Identification	Part No.	Drawing	Dimensions in mm
<b>Panel feed-through set category of transmission Cat. 5</b>  incl. housing bulkhead mounting EasyInstall with integrated seal, 2 x RJ45-jack board drillings for M3  incl. housing bulkhead mounting Compact, flat seal, 2 x RJ45-jack board drillings for M2.5	09 45 245 1130 09 45 295 1130 (metal version)		
<b>Panel feed-through set category of transmission Cat. 6</b>  incl. housing bulkhead mounting EasyInstall with integrated seal, 2 x RJ45-jack board drillings for M3  incl. housing bulkhead mounting Compact, with integrated seal, 2 x RJ45-jack	09 45 245 1102   09 45 245 1590   09 45 245 1560		