


Cables

Industrial Cat. 5 stranded cable, 4-wire,
useable as trailing cables,
Type C

to connect to mobile equipment
to make up PROFINET / SERCOS III system cables



IP 20	<input type="checkbox"/>	IP 65 / IP 67	<input type="checkbox"/>	PUR	Cat. 5	<input checked="" type="checkbox"/>	Cat. 6	<input type="checkbox"/>
-------	--------------------------	---------------	--------------------------	-----	--------	-------------------------------------	--------	--------------------------

Cable structure	Star quad, double shielding
Core structure	4 x AWG 22/7, stranded
Wire insulation	PE, Ø 1.5 mm
Sheath material	PUR
Cable sheath diameter	6.5 mm
Transmission performance	Category 5 / Class D up to 100 MHz according to ISO/IEC 11 801:2002, EN 50 173-1
Transmission rate	10/100 Mbit/s
Shielding	Shielding foil and shielding braid
Operating temperature range	-40 °C ... +70 °C
Standard lengths	20 m / 50 m / 100 m / 500 m
Colour	Green (PROFINET) Red (SERCOS III)
Printing	HARTING specific printing
Advantages	<p>Robust design suitable for industry</p> <p>PROFINET compliant (Green)</p> <p>SERCOS III compliant (Red)</p> <p>Useable as trailing cables</p> <p>Easy stripping of cable sheath and screening braid with stripping tool 09 45 800 0000</p> <p>RoHS compliant</p>

Identification	Part number		Drawing	Dimensions in mm
	PUR	SERCOS III PUR		
Industrial Cat. 5 stranded cable, 4-wire, useable as trailing cables, Type C				
	Green	Red		
20 m ring	09 45 600 0131	09 45 600 0137		
50 m ring	09 45 600 0141	09 45 600 0147		
100 m ring	09 45 600 0101	09 45 600 0107		
500 m drum	09 45 600 0111	09 45 600 0117		