


ZCKY51

limit switch lever ZCKY - metal square rod lever
3 mm L=125 mm - -40..120 °C



Main

| | |
|----------------------------|---|
| Commercial Status | Commercialised |
| Range of product | OsiSense XC |
| Series name | Standard format |
| Product or component type | Limit switch lever |
| Device short name | ZCKY |
| Product compatibility | XCKJ |
| Associated head | ZCKE05 |
| Movement of operating head | Rotary |
| Type of operator | Rod lever spring return metal (square rod 3 mm, L = 125 mm) |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|--------------------|
| Switch actuation | By any moving part |
| Positive opening | Without |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -40...20 °C for low temperature -25...70 °C for standard environment 20...120 °C for high temperature |
| Ambient air temperature for storage | -25...70 °C for standard environment -25...70 °C for low temperature -25...70 °C for high temperature |
| Environmental characteristic | High temperature Low temperature Standard environment |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.