

Main

| | |
|-----------------------------------|--|
| Commercial Status | Commercialised |
| Range of product | OsiSense XM |
| Pressure sensor type | Electromechanical pressure sensor |
| Pressure sensor name | XMP |
| Pressure sensor size | 12 bar |
| Fluid connection type | G 3/8 (female) conforming to ISO 228 |
| Controlled fluid | Sea water (0...70 °C) Fresh water (0...70 °C) Air (0...70 °C) |
| Cable entry | 2 entries incorporating Pg 13.5 plastic cable gland, cable outer diameter: 9...13 mm conforming to NF C 68-300 |
| Contacts type and composition | 3 NC snap action |
| Product specific application | - |
| Pressure switch type of operation | Regulation between 2 thresholds |
| Electrical connection | Screw-clamp terminals, clamping capacity: minimum : 2 x 4 mm ² |
| Electrical circuit type | Power circuit |
| Scale type | Adjustable differential |
| Local display | Without |
| Sale per indivisible quantity | 1 |

Complementary

| | |
|---|--|
| Adjustable range of switching point on falling pressure | 0.3...10.3 bar |
| Adjustment range high setting | 1.3...12 bar |
| Possible differential minimum at low setting | 1 bar |
| Possible differential minimum at high setting | 1.7 bar |
| Possible differential maximum at high setting | 8.4 bar |
| Destruction pressure | 30 bar |
| Type of decompression valve | Straight valve instant connection |
| Control type | ON/OFF knob |
| Terminal block type | 6 terminals |
| Pressure actuator | Diaphragm |
| Materials in contact with fluid | Canvas covered nitrile Chromated zinc alloy |
| Enclosure material | PA impregnated with fibreglass |
| Operating position | Any position |
| Operating rate | 10 cyc/mn |
| Repeat accuracy | < 3.5 % |
| [Ui] rated insulation voltage | 500 V conforming to EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-1 |
| Resistance across terminals | <= 25 MOhm conforming to NF C 93-050 method A <= 25 MOhm conforming to IEC 60255-7 category 3 |

| | |
|-------------------------------|---|
| Electrical durability | 700000 cycles (2.2 kW, operating rate: 10 cyc/mn, load factor: 0.4, 400 V AC 3 phases) 600000 cycles (1.5 kW, operating rate: 10 cyc/mn, load factor: 0.4, 230 V AC 3 phases) 500000 cycles (3 kW, operating rate: 10 cyc/mn, load factor: 0.4, 400 V AC 3 phases) 1000000 cycles (1.5 kW, operating rate: 10 cyc/mn, load factor: 0.4, 400 V AC 3 phases) |
| Mechanical durability | 1000000 cycles |
| Setting | Knurled knob and nut |
| Product weight | 0.45 kg |
| Terminals description ISO n°1 | (1-2)NC (3-4)NC (5-6)NC |
| CAD overall depth | 98 mm |
| CAD overall height | 136 mm |
| CAD overall width | 57 mm |

Environment

| | |
|--|--|
| Standards | CE EN/IEC 60947-4-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Vibration resistance | 3 gn (f = 10...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn conforming to IEC 60068-2-27 |
| Class of protection against electric shock | Class I conforming to IEC 60536 |
| IP degree of protection | IP54 conforming to EN/IEC 60529 |

RoHS compliance

| | |
|-----------------------------------|-----------|
| RoHS EUR status | Compliant |
| RoHS EUR conformity date(Y Y W W) | 0627 |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|