

# Industrial Ethernet Switch - FL SWITCH SFN 8TX - 2891929

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ethernet switch, 8 TP RJ45 ports, automatic detection of data transmission speed of 10/100 Mbps (RJ45), autocrossing function

## Product Features

- Auto negotiation and autocrossing detection simplifies installation and setup
- Local diagnostic indicators with LEDs
- The switch also offers cable locking and port blocking
- Data flow control can be disabled to locate network device errors
- QoS-prioritized (Quality of Service) messages
- RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps
- DC and AC power supplies

## Ethernet

## Key commercial data

package_quantity	1
GTIN	4046356100823

## Technical data

### Dimensions

Width	50 mm
Height	120 mm
Depth	70 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (up to 1500 m above mean sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above mean sea level)
Noise immunity	EN 61000-6-2:2005

### Interfaces

Interface 1	Ethernet (RJ45)
No. of ports	8 (RJ45 ports)

# Industrial Ethernet Switch - FL SWITCH SFN 8TX - 2891929

## Technical data

### Interfaces

<b>Connection method</b>	RJ45
<b>Note on connection method</b>	Auto negotiation and autocrossing
<b>Transmission physics</b>	Ethernet in RJ45 twisted pair
<b>Transmission speed</b>	10/100 MBit/s

### Function

<b>Basic functions</b>	Unmanaged switch / autonegotiation, complies with IEEE 802.3, store and forward switching mode
<b>Status and diagnostic indicators</b>	LEDs: U <sub>S1</sub> , link and activity per port

### Network expansion parameters

<b>Cascading depth</b>	Network, linear, and star structure: any
<b>Maximum conductor length (twisted pair)</b>	100 m

### Supply voltage

<b>Supply voltage</b>	24 V DC
<b>Residual ripple</b>	3.6 V <sub>PP</sub> (within the permitted voltage range)
<b>Supply voltage range</b>	9 V DC ... 30.2 V DC
<b>Typical current consumption</b>	typ. 140 mA

### General

<b>Mounting type</b>	DIN rail
<b>Type AX</b>	Block design
<b>Weight</b>	365 g
<b>Housing material</b>	Aluminum
<b>Noise emission</b>	EN 61000-6-4

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27250501
<b>eCl@ss 4.1</b>	27250501
<b>eCl@ss 5.0</b>	27250501
<b>eCl@ss 5.1</b>	27250501
<b>eCl@ss 6.0</b>	19170106
<b>eCl@ss 7.0</b>	19170106
<b>eCl@ss 8.0</b>	19170106

### ETIM

<b>ETIM 2.0</b>	EC000734
<b>ETIM 3.0</b>	EC000734
<b>ETIM 4.0</b>	EC000734
<b>ETIM 5.0</b>	EC000734

### UNSPSC

# Industrial Ethernet Switch - FL SWITCH SFN 8TX - 2891929

## classifications




### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201410
UNSPSC 13.2	43201410

## approvals

UL Listed / cUL Listed / cULus Listed / UL Listed / cUL Listed / cULus Listed /

### Approval details



## accessories

### Patch cable

## Industrial Ethernet Switch - FL SWITCH SFN 8TX - 2891929

### accessories

FL CAT5 PATCH 0,3 - 2832250



---

FL CAT5 PATCH 0,5 - 2832263



---

FL CAT5 PATCH 1,0 - 2832276



---

FL CAT5 PATCH 1,5 - 2832221



---

FL CAT5 PATCH 2,0 - 2832289



---

FL CAT5 PATCH 3,0 - 2832292



## Industrial Ethernet Switch - FL SWITCH SFN 8TX - 2891929

### accessories

---

FL CAT5 PATCH 5,0 - 2832580



FL CAT5 PATCH 7,5 - 2832616



FL CAT5 PATCH 10,0 - 2832629



### Protective cap

FL RJ45 PROTECT CAP - 2832991



### End block

E/NS 35 N - 0800886



### Safety locking

---

# Industrial Ethernet Switch - FL SWITCH SFN 8TX - 2891929

accessories

FL SEC PAC 4TX - 2832865



---

## Drawings

© Phoenix Contact 2014 - all rights reserved  
<http://www.phoenixcontact.com>