

Bus coupler - IBS ST 24 BK-T - 2754341

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



INTERBUS-ST bus terminal module, 24 V DC, 9-pos., D-SUB plug, IP20 protection, consisting of: Terminal part with screw connection and module electronics

The illustration shows version IBS ST 24 BK-LK

Product Description

INTERBUS ST standard bus terminal modules The INTERBUS bus terminal module connects the input/output modules of an ST station with the INTERBUS network. Depending on the transmission medium used, the bus terminal modules are equipped with different bus connections. For copper conductors, D-SUB and MINI-COMBICON connectors are available. The fiber optic versions are equipped with F-SMA connectors. The bus terminal modules are available in two different performance classes. A maximum of 4 or 8 input/output modules can be operated on one bus terminal module. The bus terminal module takes on the following functions within a modular INTERBUS-ST station: - Refreshing the INTERBUS remote bus signals - Electrical isolation of the remote bus segments - Decoupling of the outgoing remote bus or of the connected input/ output modules from the INTERBUS network with a software command - Supply of the connected input/output modules with an electrically isolated voltage supply from an integrated power supply unit

Product Features

- Up to 8 I/O modules can be connected
- Copper or fiber optic connection



Key commercial data

package_quantity	1
GTIN	4017918063108

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	81 mm
Height	116 mm
Depth	116 mm

Ambient conditions

Ambient temperature (operation)	0 °C ... 55 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Permissible humidity (operation)	30 % ... 75 % (non-condensing)

Bus coupler - IBS ST 24 BK-T - 2754341

Technical data

Ambient conditions

Permissible humidity (storage/transport)	30 % ... 95 % (On average, non-condensing)
Air pressure (operation)	86 kPa ... 108 kPa (up to 1500 m above mean sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3500 m above mean sea level)
Degree of protection	IP20

Interfaces

Fieldbus system	INTERBUS
Designation	INTERBUS remote bus
Connection method	9-pos. D-SUB plug/socket
Designation connection point	Incoming/Outgoing Remote Bus
Number of positions	9
Fieldbus system	Lokalbus
Designation	ST local bus
Connection method	ST local bus connector
Transmission speed	500 kBit/s

Digital inputs

Connection method	Screw connection
--------------------------	------------------

Power supply for module electronics

Supply voltage	24 V DC
Supply voltage range	18.5 V DC ... 30.5 V DC (including ripple)
Ripple	3.6 V _{pp} within the allowable voltage range
Current consumption	typ. 150 mA (without ST module expansions)

General

Weight	470 g
Mounting type	DIN rail
Protection class	III, IEC 61140, EN 61140, VDE 0140-1
Test section	Incoming remote bus / Outgoing remote bus 500 V AC 50 Hz 1 min
Test section	Supply voltage/Ground conductor 500 V AC 50 Hz 1 min
Test section	Incoming remote bus/ST interface 500 V AC 50 Hz 1 min

classifications

eCl@ss

eCl@ss 4.0	27250203
eCl@ss 4.1	27250203
eCl@ss 5.0	27250203
eCl@ss 5.1	27242608
eCl@ss 6.0	27242608
eCl@ss 7.0	27242608
eCl@ss 8.0	27242608

Bus coupler - IBS ST 24 BK-T - 2754341

classifications

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC001604


UNSPSC


UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404


approvals

UL Recognized / cUL Recognized / GOST / INTERBUS CLUB / cULus Recognized /

Approval details

UL Recognized 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	30-12


cUL Recognized 	
Nominal voltage UN	
Nominal current IN	
mm ² /AWG/kcmil	30-12

GOST 

INTERBUS CLUB

Bus coupler - IBS ST 24 BK-T - 2754341

approvals

cULus Recognized  US

accessories

I/O component

IBS STME 24 BK-T - 2754367



Fuse

IBS TR5 1AT - 2806600



Bridge

IB ST LBC - 2836492



EB 84 IB ST BU - 2836269



Bus coupler - IBS ST 24 BK-T - 2754341

accessories

EB 84 IB ST RD - 2836272




accessories

IBS STTB 24 BK-T - 2753180

Drawings

Bus coupler - IBS ST 24 BK-T - 2754341

Connection diagram



Bus coupler - IBS ST 24 BK-T - 2754341

Dimensioned drawing

