



Main

Circuit breaker application	Distribution
Range of product	DPN
Product or component type	Circuit breaker
Device short name	DPN N
Poles description	1P + N
Number of protected poles	1
Neutral position	Left
[In] rated current	25 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B
Breaking capacity	6000 A Icn conforming to EN 60898 - 230 V AC 50/60 Hz

Complementary

Network frequency	50/60 Hz
Magnetic tripping limit	3...5 x In
Limitation class	3 conforming to EN 60898
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
Comb busbar distribution block compatibility	YES
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	70 mm
Product weight	0.12 kg
Mechanical durability	20000 cycles
Electrical durability	15000 cycles conforming to EN 60898
Connections - terminals	Tunnel type terminals rigid wire(s) 16 mm ² max Tunnel type terminals for 2 flexible wire(s) 10 mm ² max
Wire stripping length	13 mm
Tightening torque	2 N.m

Environment

IP degree of protection	IP201 conforming to EN 60898 IP4 conforming to EN 60898
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % 55 °C
Operating altitude	2000 m

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

RoHS	Compliant - since 0707 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations