



Main

Product or component type	Earth leakage protection
Poles description	4P
Neutral position	Left
[In] rated current	40 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class B
Rated breaking and making capacity	Im 500 A conforming to IEC 61008
Rated conditional short-circuit current	I _{nc} 10 kA 40 A

Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[U _e] rated operational voltage	230/400 V
9 mm pitches	8
Product weight	0.5 kg
Colour	Grey
Mechanical durability	< 5000 cycles
Electrical durability	< 2000 cycles
Connections - terminals	Tunnel type terminals 1 cable(s) 1.5...60 mm ² flexible Tunnel type terminals 1 cable(s) 1.5...60 mm ² rigid Tunnel type terminals 2 cable(s) 1.5...16 mm ² flexible Tunnel type terminals 2 cable(s) 1.5...16 mm ² rigid

Environment

Standards	EN 61008 IEC 61008 VDE 0664
Tropicalisation	2
Relative humidity	95 % (55 °C)
Ambient air temperature for operation	-25...40 °C
Ambient air temperature for storage	-40...60 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0740 - Schneider Electric declaration of conformity
Product end of life instructions	Need no specific recycling operations