

Main

Range of product	ID RCCB
Product or component type	Earth leakage protection
Device short name	ID RCCB
Poles description	4P
Neutral position	Left
[In] rated current	63 A
Network type	AC
Earth-leakage sensitivity	500 mA
Earth-leakage protection time delay	Selective
Earth-leakage protection class	Class AC
Rated breaking and making capacity	Im 630 A
Rated conditional short-circuit current	Inc 10 kA 63 A

Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	400 V AC 50/60 Hz conforming to IEC 61008
Residual current tripping technology	Electromechanical
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-3
Control type	Toggle
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	8
Height	81 mm
Width	72 mm
Depth	75 mm
Product weight	0.45 kg
Mechanical durability	20000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminals 1...35 mm ² rigid Tunnel type terminals 1...25 mm ² flexible
Wire stripping length	15 mm
Tightening torque	3.5 N.m

Environment

Standards	IEC 60947-1 IEC 60947-3 IEC 61008
Tropicalisation	2 conforming to IEC 61008
Relative humidity	95 % (55 °C)
Operating altitude	2000 m
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-40...60 °C

Contractual warranty

Period	18 months
--------	-----------
