



### Main

Circuit breaker application	Distribution
Range	Multi 9
Product or component type	Earth leakage circuit breaker
Product name	DPN Vigi
Device short name	DPN N Vigi
Poles description	1P + N
Neutral position	Left
[In] rated current	6 A ( 30 °C )
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class AC
Breaking capacity	Icn 6 kA at 240 V AC conforming to EN 61009 Icn 6000 A at 240 V AC conforming to EN 60898

### Complementary

Device location in system	Outgoer
[Ue] rated operational voltage	230 V AC
Magnetic tripping limit	5...10 x In
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting support	DIN rail
9 mm pitches	4
Product weight	0.19 kg
Mechanical durability	20000 cycles
Electrical durability	20000 cycles conforming to IEC 61009
Connections - terminals	Tunnel type terminals 1 cable(s) 10 mm <sup>2</sup> flexible Tunnel type terminals 1 cable(s) 16 mm <sup>2</sup> rigid
Earth-leakage protection	Integrated

### Environment

Standards	EN 60898 EN 61009
Tropicalisation	2
Relative humidity	95 % ( 55 °C )

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0712 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

