


| | | |
|----------------|--------------------------------|--|
| U.I. Lapp GmbH | PRODUCT INFORMATION |  |
| | ÖLFLEX® SERVO FD 798 CP | 29.11.2013 |

High-end resolver/encoder cable, screened
Thin, optimised for weight and volume
Also suitable for mobile outdoor use
Suitable for use with encoders & resolvers from leading manufacturers
To substitute 4 ÖLFLEX® SERVO FD product lines: -760CP/-760CP DESINA@/-770CP/ -770CP DESINA@



Halogen-free



Mechanical resistance



Oil-resistant



Power chain



Interference signals



UV-resistant

Info

Extended Line for heavy duty in power chain applications
EMC-compliant


Application range

Connecting cable between servo controller and encoder/resolver
Connecting cable between servo controller and speed generators
In power chains or moving machine parts
Particularly in wet areas of machine tools and transfer lines
Assembly lines, production lines, in all kinds of machines

Design

Fine-wire or extra-fine wire, tinned-copper conductor
Core insulation: polypropylene (PP)
Cores (or core pairs) twisted in layers or bundles
Refer to data sheet for more details
Non-woven wrapping
PUR outer sheath, green (RAL 6018)

| | | |
|--------------------|--------------------------------|-------|
| Product Management | Document: LAPP_PRO209469EN.pdf | 1 / 3 |
|--------------------|--------------------------------|-------|

| | | |
|-------------------|--------------------------------|--|
| U.I. Lapp GmbH | PRODUCT INFORMATION |  |
| | ÖLFLEX® SERVO FD 798 CP | 29.11.2013 |

Norm references / Approvals

UL AWM Style 20236

CSA AWM IA/B; IIA/B FT 1

For use in power chains: Please comply with the assembly guidelines listed in Appendix T3

UL File No. E63634

Product features

Dynamic performance in power chains: Acceleration up to 50 m/s². Travel speeds up to 5 m/s. Travel distances up to 100 m.

Low-capacitance design

Halogen-free materials

Flame retardancy: UL/CSA: VW-1, FT1 IEC/EN: 60332-1-2

Oil-resistant

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

DESINA® is a registered trademark of the German Machine Tool Builders' Association

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

| | |
|---------------------------------|---|
| Core identification code: | Details see datasheet ÖLFLEX® SERVO FD 798 CP |
| Classification: | ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable |
| Specific insulation resistance: | > 20 GOhm x cm |
| Conductor stranding: | Fine wire or extra-fine wire |
| Minimum bending radius: | Flexible use: 7.5 x outer diameter Fixed installation: 4 x outer diameter |
| Nominal voltage: | IEC: 30 V UL & CSA: 30 V |
| Test voltage: | Core/core: 1500 V rms Core/screen: 750 V rms |
| Temperature range: | Flexing: -40°C to +90°C (UL/CSA: +80°C) Fixed installation: -50°C to +90°C (UL/CSA: +80°C) |

| | | |
|--------------------|--------------------------------|-------|
| Product Management | Document: LAPP_PRO209469EN.pdf | 2 / 3 |
|--------------------|--------------------------------|-------|

ÖLFLEX® SERVO FD 798 CP

29.11.2013

| Part number | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------|---|---------------------|----------------------|----------------|
| ÖLFLEX® SERVO FD 798 CP | | | | |
| 0036910 | 4x2x0,34+4x0,5 | 8.9 | 79.0 | 125 |
| 0036911 | 3x(2x0,14)+2x(0,5) | 8.9 | 70.0 | 120 |
| 0036912 | 3x(2x0,14)+4x0,14+2x0,5 | 8.8 | 68.0 | 110 |
| 0036913 | 3x(2x0,14)+4x0,14+2x0,5+4x0,22 | 9.4 | 80.0 | 130 |
| 0036914 | 9x0,5 | 8.8 | 71.0 | 110 |
| 0036915 | 4x2x0,25+2x1,0 | 8.8 | 63.0 | 109 |
| 0036916 | 6x2x0,25+2x0,5 | 10.3 | 67.0 | 121 |
| 0036917 | 10x0,14+2x0,5 | 7.7 | 41.0 | 82 |
| 0036918 | 10x0,14+4x0,5 | 8.1 | 54.0 | 98 |
| 0036920 | 4x2x0,14+4x0,5 | 8.2 | 51.0 | 95 |
| 0036921 | 4x2x0,25 | 7.6 | 38.0 | 75 |
| 0036923 | 8x2x0,18 | 7.8 | 51.0 | 85 |
| 0036924 | 4x2x0,18 | 6.4 | 30.0 | 52 |
| 0036926 | 12x0,22 | 6.9 | 44.0 | 73 |
| 0036927 | 4x2x0,25+2x0,5 | 8.5 | 62.0 | 98 |
| 0036928 | 2x2x0,14+2x(2x0,14)+4x0,5+(4x0,14) | 9.1 | 79.0 | 135 |
| 0036929 | 2x(2x0,25)+2x0,5 | 8.7 | 46.0 | 98 |
| 0036930 | 2x2x0,25+2x0,5 | 7.3 | 38.0 | 72 |