


U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SKINDICHT® MR-M</b>	29.11.2013

Enables the use of cable glands with smaller connection threads than the existing threaded holes



Space requirement



Reliability



Connector with standard housing unit

### Application range

Machines  
Devices  
Housings

### Design

Metric connection thread acc. to EN 50262

### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

### Technical Data

On request:	Also available with pre-installed O-ring
Material:	Nickel-plated brass
Temperature range:	-60°C to +200°C

Product Management	Document: LAPP_PRO1033EN.pdf	1 / 2
--------------------	------------------------------	-------



**SKINDICHT® MR-M**

29.11.2013

Part number	Thread/ male M1	Thread/ female M2	Overall length/ C (mm)	Thread length/ D (mm)	Outer Ø (mm)
<b>SKINDICHT® MR-M</b>					
52104310	16 x 1.5	12 x 1.5			
52104311	20 x 1.5	12 x 1.5			
52104312	20 x 1.5	16 x 1.5			
52104313	25 x 1.5	16 x 1.5			
52104314	25 x 1.5	20 x 1.5			
52104315	32 x 1.5	20 x 1.5			
52104316	32 x 1.5	25 x 1.5			
52104317	40 x 1.5	25 x 1.5			
52104318	40 x 1.5	32 x 1.5			
52104319	50 x 1.5	32 x 1.5			
52104320	50 x 1.5	40 x 1.5			
52104321	63 x 1.5	40 x 1.5			
52104322	63 x 1.5	50 x 1.5			
<b>SKINDICHT® MR-M, blank brass</b>					
52006579	80 x 2	75 x 1.5	19.0	12.0	86.0
<b>SKINDICHT® MR-M, nickel-plated brass</b>					
52006575	72 x 2	63 x 1.5	19.0	12.0	78.0