

## Main

Circuit breaker application	Distribution
Range of product	C60
Device short name	C60H
Poles description	1P
Number of protected poles	1
Network type	AC DC
Trip unit technology	Thermal-magnetic
Curve code	B
Suitability for isolation	Yes IEC 60947-2

## Complementary

[In] rated current	1 A 30 °C
Network frequency	50/60 Hz
[Ue] rated operational voltage	12...440 V AC 50/60 Hz
Magnetic tripping limit	3...5 x In
Breaking capacity	4 kA Icu IEC 60947-2 400...415 V AC 50/60 Hz 30 kA Icu IEC 60947-2 130 V AC 50/60 Hz 20 kA Icu IEC 60947-2 60 V DC 1P 15 kA Icu IEC 60947-2 230...240 V AC 50/60 Hz 10 kA Icn EN 60898 230/400 V AC 50/60 Hz
[Ics] rated service breaking capacity	7.5 kA EN 60898 230/400 V AC 50/60 Hz 7.5 kA IEC 60947-2 230...240 V AC 50/60 Hz 25 kA IEC 60947-2 130 V AC 50/60 Hz 2 kA IEC 60947-2 400...415 V AC 50/60 Hz
Limitation class	3 IEC 60947-2
[Ui] rated insulation voltage	500 V AC 50/60 Hz IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Comb busbar distribution block compatibility	NO
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	73 mm
Product weight	0.12 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals 25 mm <sup>2</sup> rigid Tunnel type terminals 16 mm <sup>2</sup> flexible
Tightening torque	2 N.m upside power circuit 2 N.m downside
Product compatibility	C60 accessories C60 auxiliary

## Environment

Standards	EN 60898 IEC 60947-2
Tropicalisation	2 IEC 60068-1
Relative humidity	95 % 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

## Contractual warranty

Period	18 months
--------	-----------