

Main

Circuit breaker application	Distribution
Range of product	C60
Device short name	C60H
Poles description	1P
Number of protected poles	1
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Suitability for isolation	Yes IEC 60947-2

Complementary

[In] rated current	25 A 30 °C
Network frequency	50/60 Hz
[Ue] rated operational voltage	230...240 V AC 50/60 Hz
Magnetic tripping limit	5...10 x In
Breaking capacity	10 kA AC
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	70 mm
Product weight	0.12 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals <= 25 mm ² stranded Tunnel type terminals <= 16 mm ² flexible

Environment

Standards	AS Nzs 60898
IP degree of protection	IP40 IP20
Tropicalisation	2
Relative humidity	95 % 55 °C
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-40...100 °C

Contractual warranty

Period	18 months
--------	-----------